DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer Product line : W21 Explosion Proof High Efficiency Three-Product code: 11124468 : 586/7T Locked rotor time Frame : 133s (cold) 74s (hot) Output : 250 HP (185 kW) Temperature rise : 80 K Poles Duty cycle : Cont.(S1) Frequency : 60 Hz Ambient temperature : -20°C to +40°C : 460 V Rated voltage Altitude : 1000 m.a.s.l. Rated current : 305 A Protection degree : IP55 : IC411 - TEFC L. R. Amperes : 1830 A Cooling method **LRC** : 6.0x(Code G) Mounting : F-1 : Both (CW and CCW) No load current : 106 A Rotation¹ Rated speed : 1190 rpm Noise level² : 77.0 dB(A) Slip : 0.83 % Starting method : Direct On Line Rated torque : 1100 ft.lb Approx. weight³ : 3913 lb Locked rotor torque : 180 % Breakdown torque : 210 % : F Insulation class Service factor : 1.15 Moment of inertia (J) : 226 sq.ft.lb Design 25% 50% 75% Output 100% Foundation loads Efficiency (%) 92.1 93.0 94.1 95.0 Max. traction : 2877 lb Power Factor 0.45 0.68 0.76 0.80 Max. compression : 6790 lb Non drive end Drive end Bearing type 6322 C3 6319 C3 Viton Oil Seal Viton Seal Sealing Lubrication interval 9212 h 11094 h Lubricant amount 60 g 45 g Lubricant type Mobil Polyrex EM

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.

(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	27/03/2024			1/2	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



_	
Customer	
Custoffici	

Thermal protection

		•		
ID	Application	Туре	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary Performed		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	27/03/2024			2/2	