

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W21 Explosion Proof NEMA Premium
Efficiency Three-Phase

Product code : 14293169

Catalog # : 00158XT3ER145TC

Frame	: 143/5TC	Locked rotor time	: 25s (cold) 14s (hot)
Output	: 1.5 HP (1.1 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 4.10/2.05 A	Protection degree	: IP55
L. R. Amperes	: 36.5/18.2 A	Cooling method	: IC411 - TEFC
LRC	: 8.9x(Code L)	Mounting	: W-6
No load current	: 2.40/1.20 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1755 rpm	Noise level ²	: 51.0 dB(A)
Slip	: 2.50 %	Starting method	: Direct On Line
Rated torque	: 4.49 ft.lb	Approx. weight ³	: 73.1 lb
Locked rotor torque	: 270 %		
Breakdown torque	: 350 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.1303 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads					
Efficiency (%)	80.2	83.7	81.5	84.0	85.5	84.0	86.5	84.0	Max. traction	: 114 lb
	83.7	80.9	84.0	82.5	84.0	84.0	84.0	85.5		
Power Factor	0.34	0.39	0.58	0.66	0.70	0.77	0.78	0.83	Max. compression	: 189 lb
	0.35	0.33	0.62	0.58	0.74	0.71	0.81	0.79		

					<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:				6205 2RS	6204 2RS
Sealing	:				Oil Seal	Lip Seal
Lubrication interval	:				-	-
Lubricant amount	:				-	-
Lubricant type	:				Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	27/03/2024			
			Page	Revision
			1 / 2	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date	27/03/2024				