DATA SHEET

:

Three Phase Induction Motor - Squirrel Cage



Customer

		: W21 Explosion Proof NEMA Premiur Efficiency Three-Phase					14653232	
					(Catalog # :	20012XT3H	4471
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor tor Breakdown torq Insulation class Service factor Moment of inerti Design	ue	: 6 : 60 F : 575 : 199 : 1554 : 7.8x : 100 : 1190 : 0.83 : 883 : 270 : 280 : F : 1.15	HP (150 k Iz V A 4 A (Code J) A 0 rpm 3 % ft.lb % %	:W)	Tempera Duty cy Ambien Altitude Protecti Cooling Mountin Rotation Noise le Starting	t temperature on degree method ¹⁹	: 25s (cold) : 80 K : Cont.(S1) : -20°C to + : 1000 m.a. : IP55 : IC411 - TE : F-1 : Both (CW : 73.0 dB(A : Direct On : 200 lb	40°C s.l. EFC and CCW)
Dutput	25%	50%	75%	100%	Foundatio	on loads		
Efficiency (%) Power Factor	94.0 0.35	94.5 0.60	95.4 0.73	95.8 0.79	Max. tract Max. com	tion	: 6488 lb : 6688 lb	
Sealing Lubrication inter Lubricant amour		•	11	Oil Seal 094 h		Lip Seal 12823 h		
Lubricant type Notes: This revision rep nust be eliminate 1) Looking the n 2) Measured at	laces and c ed. notor from 1	the shaft e h tolerance	previous c nd. e of +3dB(one, which A).		34 g EM e average values pply, subject to the		
Lubricant type Notes: This revision rep must be eliminate 1) Looking the n 2) Measured at 3) Approximate manufacturing pr 4) At 100% of fu	laces and o ed. notor from t 1m and wit weight sub rocess.	the shaft e h tolerance ject to cha	previous c nd. e of +3dB(nges after	one, which A).	These arr power su	EM e average values pply, subject to the	e tolerances stipu	lated in NEMA
Lubricant type Notes: This revision rep nust be eliminate 1) Looking the n 2) Measured at 3) Approximate nanufacturing pr	laces and o ed. notor from t 1m and wit weight sub rocess.	the shaft e h tolerance ject to cha	previous c nd. e of +3dB(one, which A).	These arr power su	EM e average values		
Lubricant type Notes: This revision rep nust be eliminate 1) Looking the n 2) Measured at 3) Approximate nanufacturing pr 4) At 100% of fu Rev.	laces and o ed. notor from t 1m and wit weight sub rocess.	the shaft e h tolerance ject to cha	previous c nd. e of +3dB(nges after	one, which A).	These arr power su	EM e average values pply, subject to the	e tolerances stipu	lated in NEMA
Lubricant type Notes: This revision rep nust be eliminate 1) Looking the n 2) Measured at 3) Approximate nanufacturing pr 4) At 100% of fu	laces and o ed. notor from t 1m and wit weight sub rocess.	the shaft e h tolerance ject to cha	previous c nd. e of +3dB(nges after	one, which A).	These arr power su	EM e average values pply, subject to the	e tolerances stipu	lated in NEMA

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A. Subject to change without notice

DATA SHEET

Three Phase Induction Motor - Squirrel Cage

:

Customer

ID	Application	Туре	Quantity	Sensing	Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	1	55 °C
	v				
Rev.	Changes	Summary	Performed	Checked	Date
		· (-
rformed by					
rformed by				_	
				Page	Devictor
hecked by	28/03/2024			2/2	Revision

