

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W21 NEMA Premium Efficiency Three-Phase Product code : 10673195

Frame	: 184Y	Locked rotor time	: 46s (cold) 26s (hot)
Output	: 5 HP (3.7 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 208-230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 13.2-11.9/5.96 A	Protection degree	: IP55
L. R. Amperes	: 119-107/53.6 A	Cooling method	: IC418 - TEAO
LRC	: 9.0x(Code K)	Mounting	: F-1
No load current	: 4.14-4.80/2.40 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3510 rpm	Noise level ²	: 69.0 dB(A)
Slip	: 2.50 %	Starting method	: Direct On Line
Rated torque	: 7.48 ft.lb	Approx. weight ³	: 107 lb
Locked rotor torque	: 280 %		
Breakdown torque	: 380 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 0.2361 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads					
Efficiency (%)	85.3	87.0	86.5	86.5	88.5	87.5	89.5	86.5	Max. traction	: 149 lb
	87.0	86.1	86.5	86.5	88.5	88.5	87.5	88.5		
Power Factor	0.45	0.50	0.70	0.75	0.80	0.84	0.87	0.90	Max. compression	: 256 lb
	0.47	0.44	0.72	0.69	0.82	0.80	0.88	0.87		

					<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:				6307 ZZ	6206 ZZ
Sealing	:				V'Ring	V'Ring
Lubrication interval	:				-	-
Lubricant amount	:				-	-
Lubricant type	:				Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	28/03/2024			
			Page	Revision
			1 / 1	