

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W21 Explosion Proof NEMA Premium
Efficiency Three-Phase

Product code : 11963107

Catalog # : 25018XT3G447T

Frame	: 447T	Locked rotor time	: 36s (cold) 20s (hot)
Output	: 250 HP (185 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 284 A	Protection degree	: IP55
L. R. Amperes	: 1988 A	Cooling method	: IC411 - TEFC
LRC	: 7.0x(Code H)	Mounting	: F-1
No load current	: 90.3 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1784 rpm	Noise level ²	: 82.0 dB(A)
Slip	: 0.89 %	Starting method	: Direct On Line
Rated torque	: 736 ft.lb	Approx. weight ³	: 2598 lb
Locked rotor torque	: 250 %		
Breakdown torque	: 250 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 89.6 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads					
Efficiency (%)	95.3	94.5	95.4	95.0	96.2	95.4	96.2	95.8	Max. traction	: 4726 lb
	95.3	95.3	95.4	95.4	95.8	95.8	95.8	95.8		
Power Factor	0.49	0.49	0.72	0.72	0.81	0.81	0.85	0.85	Max. compression	: 7325 lb
	0.45	0.42	0.69	0.66	0.79	0.77	0.84	0.83		

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6319 C3	6316 C3
Sealing	:	Viton Oil Seal	Viton Seal
Lubrication interval	:	7038 h	8569 h
Lubricant amount	:	45 g	34 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 2 Revision		
Checked by				
Date	28/03/2024			

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by					
Date	28/03/2024			2 / 2	