

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Brake Motor NEMA Premium Efficiency Three-Phase Product code : 13474048
Catalog # : 00509ET3EBM254T-W22

Frame	: 254/6T	Locked rotor time	: 77s (cold) 43s (hot)
Output	: 5 HP (3.7 kW)	Temperature rise	: 80 K
Poles	: 8	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 15.4/7.69 A	Protection degree	: IP55
L. R. Amperes	: 81.5/40.8 A	Cooling method	: IC411 - TEFC
LRC	: 5.3x(Code H)	Mounting	: F-1
No load current	: 10.8/5.40 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 883 rpm	Noise level ²	: 54.0 dB(A)
Slip	: 1.89 %	Starting method	: Direct On Line
Rated torque	: 29.7 ft.lb	Approx. weight ³	: 326 lb
Locked rotor torque	: 250 %		
Breakdown torque	: 280 %		
Insulation class	: F		
Service factor	: 1.25		
Moment of inertia (J)	: 3.41 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	84.0	84.7	87.0	87.5	Max. traction	: 236 lb
Power Factor	0.26	0.48	0.61	0.69	Max. compression	: 562 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
13.7	11.9	12.0	7.8	5.9	4.6	3.6

	Drive end	Non drive end
Bearing type	: 6309 C3	: 6209 C3
Sealing	: V'Ring	: Lip Seal
Lubrication interval	: 20000 h	: 20000 h
Lubricant amount	: 13 g	: 9 g
Lubricant type	: Mobil Polyrex EM	

Notes:
USABLE @208V 16.8A SF 1.15 SFA 19.3A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	29/03/2024			
		Page		Revision
		1 / 2		

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer : _____

Brake information

Voltage: 220-240 V
Brake Torque: 173 ft.lb

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 2 / 2		Revision
Checked by					
Date	29/03/2024				