

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W21 Explosion Proof NEMA Premium  
Efficiency Three-Phase

Product code : 12408387

Catalog # : 45018XT3G586/7

Frame : 586/7T  
Output : 450 HP (330 kW)  
Poles : 4  
Frequency : 60 Hz  
Rated voltage : 460 V  
Rated current : 501 A  
L. R. Amperes : 3257 A  
LRC : 6.5x(Code G)  
No load current : 121 A  
Rated speed : 1787 rpm  
Slip : 0.72 %  
Rated torque : 1320 ft.lb  
Locked rotor torque : 180 %  
Breakdown torque : 200 %  
Insulation class : F  
Service factor : 1.15  
Moment of inertia (J) : 213 sq.ft.lb  
Design : B

Locked rotor time : 43s (cold) 24s (hot)  
Temperature rise : 105 K  
Duty cycle : Cont.(S1)  
Ambient temperature : -20°C to +40°C  
Altitude : 1000 m.a.s.l.  
Protection degree : IP55  
Cooling method : IC411 - TEFC  
Mounting : F-1  
Rotation<sup>1</sup> : Both (CW and CCW)  
Noise level<sup>2</sup> : 83.0 dB(A)  
Starting method : Direct On Line  
Approx. weight<sup>3</sup> : 4404 lb

Output	25%		50%		75%		100%	
Efficiency (%)	95.7	95.7	95.8	95.8	96.2	96.2	96.2	96.2
	95.7	95.7	95.8	95.8	96.2	96.2	96.2	96.2
Power Factor	0.59	0.57	0.81	0.80	0.85	0.85	0.86	0.86
	0.54	0.51	0.78	0.75	0.83	0.82	0.85	0.85

Foundation loads  
Max. traction : 4238 lb  
Max. compression : 8630 lb

	Drive end	Non drive end
Bearing type	6322 C3	6319 C3
Sealing	Viton Oil Seal	Viton Seal
Lubrication interval	5138 h	7038 h
Lubricant amount	60 g	45 g
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 2 Revision		
Checked by				
Date	28/03/2024			

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by					
Date	28/03/2024			2 / 2	