DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer :

Product line	: Rolled Steel JP Pump High Efficiency Three-Phase	Product code :	13550884
		Catalog # :	00736OP3EFP184JPV-S

Frame	: 182/4JP	Locked rotor time	: 19s (cold) 11s (hot)
Output	: 7.5 HP (5.5 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 17.7/8.86 A	Cooling method	: IC01 - ODP
L. R. Amperes	: 124/62.0 A	Mounting	: W-6
LRC	: 7.0x(Code H)	Rotation¹	: Both (CW and CCW)
No load current	: 6.99/3.49 A	Noise level²	: 65.0 dB(A)
Rated speed	: 3500 rpm	Starting method	: Direct On Line
Slip	: 2.78 %	Approx. weight³	: 71.3 lb
Rated torque	: 11.3 ft.lb		
Locked rotor torque	: 180 %		
Breakdown torque	: 280 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.1559 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%
Efficiency (%)	88.1	87.5	88.5	87.5
Power Factor	0.47	0.74	0.84	0.89

Foundation loads	
Max. traction	: 165 lb
Max. compression	: 237 lb

		Drive end	Non drive end
Bearing type	:	6207 ZZ	6205 ZZ
Sealing	:	Without Bearing Seal	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:
USABLE @208V 19.6A SF 1.00 SFA 19.6A

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	26/03/2024		1 / 1	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice