DATA SHEET

Three Phase Induction Motor - Squirrel Cage



				-	_				
Customer	:								
Product line : W22 High Efficiency Three-Phase					Product code : Catalog # :	14412142 25015EP3OFP449TS-W22			
Frame	: 447/9	TS		Locked rotor time	: 46s (cold) 26s (hot)				
Output		IP (185 kW	Λ	Temperature rise	: 80 K				
Poles	: 4	(100 111	, ,	Duty cycle	: Cont.(S1)				
Frequency	: 50 Hz			Ambient temperature	: -20°C to +40°C				
Rated voltage	: 380 V			Altitude	: 1000 m.a.s.l.				
Rated current	: 339 A			Protection degree	: IP55				
L. R. Amperes	: 1865			Cooling method	: IC411 - TEFC				
LRC			Code E)		Mounting	: F-1			
No load current		: 91.0 A			Rotation ¹	: Both (CW and CCW)			
Rated speed		: 1475			Noise level ²	: 69.0 dB(A)			
Slip		: 1.67 %			Starting method	: Direct On Line			
Rated torque		: 890 ft.lb			Approx. weight ³	: 2800 lb			
Locked rotor torque		: 180 %							
Breakdown torque		: 210 %							
Insulation class		: F							
Service factor		: 1.15							
Moment of inertia (J)		: 112 so	q.ft.lb						
Design		: B	•						
Output	25%	50%	75%	100%	Foundation loads				
· · · · · · · · · · · · · · · · · · ·						. 4540 lb			
Efficiency (%)	0.000 0.000	95.4 95.4	95.4 95.4	95.4 95.4	Max. traction	: 4512 lb			
Power Factor	0.00 0.00	0.81 0.77	0.85 0.83	0.87 0.86	Max. compression	: 7312 lb			
			Drive		Non drive end				
Bearing type		:	6314		6314 C3				
Sealing		:	_	Seal	WSeal				
Lubrication interv		:		00 h	14000 h				
Lubricant amount : 27 g					27 g				
Lubricant type		:	Mobil Polyrex EM						

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	26/03/2024			1/1	