## **DATA SHEET**

#### Three Phase Induction Motor - Squirrel Cage



|  |                   |  |   |                   | 3   |  |
|--|-------------------|--|---|-------------------|---|--|
| Customer   | :                 |  |   |                   |   |  |
| Product line   | : W40             | High Effic                                     | ciency Thre   | e-Phase           | Product code :<br>Catalog # :   | 15692550<br>25015OP3OFP449TS-<br>W40   |
| Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor torque Breakdown torque Insulation class Service factor Moment of inertia Design | •                 | : 4<br>: 50 Hz<br>: 380 V<br>: 343 A<br>: 2195 | HP (185 kW<br>Z<br>Z<br>Z<br>A<br>Code G)<br>A<br>rpm<br>%<br>Lilb<br>6 | ()                | Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³ | : 41s (cold) 23s (hot) : 70 K : Cont.(S1) : -20°C to +50°C : 1000 m.a.s.l. : IP23 : IC01 - ODP : F-1 : Both (CW and CCW) : 72.0 dB(A) : Direct On Line : 2289 lb |
| Output   | 25%               | 50%  | 75%   | 100%              | Foundation loads  |  |
| Efficiency (%)   | 95.3 95.1<br>94.8 | 95.4 95.4<br>95.4                              | 95.4 95.4<br>95.4   | 95.4 95.4<br>95.4 | Max. traction   | : 4516 lb  |
| Power Factor   | 0.55 0.51<br>0.48 | 0.75 0.72<br>0.70                              | 0.83 0.81<br>0.80   | 0.86 0.85<br>0.84 | Max. compression  | : 6804 lb  |
| Bearing type<br>Sealing<br>Lubrication interva<br>Lubricant amount<br>Lubricant type   | ıl                | :<br>:<br>:<br>:                               | <u>Drive</u><br>6314<br>Without Be<br>450<br>27                         | aring Seal<br>0 h | Non drive end<br>6314 C3<br>Without Bearing Se<br>4500 h<br>27 g<br>bil Polyrex EM  | eal  |

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

| ,            |            |                 |    |           |         |          |
|--------------|------------|-----------------|----|-----------|---------|----------|
| Rev.         |            | Changes Summary | Pe | Performed | Checked | Date     |
|              |            |                 |    |           |         |          |
| Performed by |            |                 |    |           |         |          |
| Checked by   |            |                 |    |           | Page    | Revision |
| Date         | 26/03/2024 | 1               |    |           | 1/2     |          |

# DATA SHEET

### Three Phase Induction Motor - Squirrel Cage



| Customer |  |
|----------|--|

#### Thermal protection

|    | P           |                      |           |                     |  |  |  |
|----|-------------|----------------------|-----------|---------------------|--|--|--|
| ID | Application | Туре                 | Quantity  | Sensing Temperature |  |  |  |
| 1  | Winding     | Thermistor - 2 wires | 1 x Phase | 155 °C              |  |  |  |

| Rev.         | Changes Summary |  | Performed | Checked | Date     |
|--------------|-----------------|--|-----------|---------|----------|
|              |                 |  |           |         |          |
| Performed by |                 |  |           |         |          |
| Checked by   |                 |  |           | Page    | Revision |
| Date         | 26/03/2024      |  |           | 2/2     |          |