

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :						
Product line : W40 High Efficiency Three-Phase			Product code : 14282622			
			Catalog # : 12518OP3HFP405TS-W40			
Frame : 404/5TS Output : 125 HP Poles : 4 Frequency : 60 Hz Rated voltage : 575 V Rated current : 111 A L. R. Amperes : 723 A LRC : 6.5x(Code G) No load current : 30.4 A Rated speed : 1775 rpm Slip : 1.39 % Rated torque : 370 ft.lb Locked rotor torque : 210 % Breakdown torque : 229 % Insulation class : F Service factor : 1.15 Moment of inertia (J) : 21.5 sq.ft.lb Design : B		Locked rotor time : 21s (cold) 12s (hot) Temperature rise : 80 K Duty cycle : Cont.(S1) Ambient temperature : -20°C to +40°C Altitude : 1000 m.a.s.l. Protection degree : IP23 Cooling method : IC01 - ODP Mounting : F-1 Rotation ¹ : Both (CW and CCW) Starting method : Direct On Line Approx. weight ³ : 1046 lb				
Output	25%	50%	75%	100%		
Efficiency (%)	94.0	94.1	94.5	94.5		
Power Factor	0.54	0.76	0.84	0.86		
Foundation loads						
Max. traction : 2027 lb						
Max. compression : 3074 lb						
		<u>Drive end</u>		<u>Non drive end</u>		
Bearing type :		6314 C3		6212 Z C3		
Sealing :		Without Bearing Seal		Without Bearing Seal		
Lubrication interval :		20000 h		20000 h		
Lubricant amount :		27 g		13 g		
Lubricant type :		Mobil Polyrex EM				
Notes:						
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.			
Rev.	Changes Summary			Performed	Checked	Date
Performed by						
Checked by					Page	Revision
Date	26/03/2024				1 / 1	