

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel JM Pump NEMA Premium
Efficiency Three-Phase

Product code : 12637246

Catalog # : 00236OT3V145JM-S

Frame : 143/5JM
Output : 2 HP (1.5 kW)
Poles : 2
Frequency : 60 Hz
Rated voltage : 200/400 V
Rated current : 5.57/2.78 A
L. R. Amperes : 49.5/24.8 A
LRC : 8.9x(Code K)
No load current : 2.11/1.05 A
Rated speed : 3510 rpm
Slip : 2.50 %
Rated torque : 2.99 ft.lb
Locked rotor torque : 220 %
Breakdown torque : 330 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 0.1151 sq.ft.lb
Design : B

Locked rotor time : 25s (cold) 14s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Cooling method : IC01 - ODP
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 62.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 38.7 lb

Output	25%	50%	75%	100%
Efficiency (%)	83.7	84.0	85.5	85.5
Power Factor	0.49	0.77	0.86	0.91

Efficiency (%)	83.7	84.0	85.5	85.5
Power Factor	0.49	0.77	0.86	0.91

Foundation loads

Max. traction : 66 lb
Max. compression : 105 lb

	Drive end	Non drive end
Bearing type	6206 ZZ	6203 ZZ
Sealing	Without Bearing Seal	Without Bearing Seal
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	29/03/2024			

Page 1 / 1
Revision