DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer :

Product line	: Rolled Steel JP Pump NEMA Premium Efficiency Three-Phase	Product code :	13500647
		Catalog # :	00236OT3V145JP-S

Frame	: 143/5JP	Locked rotor time	: 25s (cold) 14s (hot)
Output	: 2 HP (1.5 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 200/400 V	Altitude	: 1000 m.a.s.l.
Rated current	: 5.57/2.78 A	Cooling method	: IC01 - ODP
L. R. Amperes	: 49.5/24.8 A	Mounting	: F-1
LRC	: 8.9x(Code K)	Rotation¹	: Both (CW and CCW)
No load current	: 2.11/1.05 A	Noise level²	: 62.0 dB(A)
Rated speed	: 3510 rpm	Starting method	: Direct On Line
Slip	: 2.50 %	Approx. weight³	: 36.8 lb
Rated torque	: 2.99 ft.lb		
Locked rotor torque	: 220 %		
Breakdown torque	: 330 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.1151 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%
Efficiency (%)	83.7	84.0	85.5	85.5
Power Factor	0.49	0.77	0.86	0.91

Foundation loads	
Max. traction	: 67 lb
Max. compression	: 104 lb

		Drive end	Non drive end
Bearing type	:	6206 ZZ	6203 ZZ
Sealing	:	Without Bearing Seal	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	29/03/2024		1 / 1	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice