

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel JM Pump High Efficiency Three-Phase Product code : 12502517

| | | | |
|-----------------------|------------------|-----------------------------|-----------------------|
| Frame | : 213/5JM | Locked rotor time | : 14s (cold) 8s (hot) |
| Output | : 10 HP (7.5 kW) | Temperature rise | : 80 K |
| Poles | : 4 | Duty cycle | : Cont.(S1) |
| Frequency | : 60 Hz | Ambient temperature | : -20°C to +40°C |
| Rated voltage | : 230/460 V | Altitude | : 1000 m.a.s.l. |
| Rated current | : 24.2/12.1 A | Protection degree | : IP55 |
| L. R. Amperes | : 165/82.3 A | Cooling method | : IC411 - TEFC |
| LRC | : 6.8x(Code H) | Mounting | : F-1 |
| No load current | : 9.78/4.89 A | Rotation ¹ | : Both (CW and CCW) |
| Rated speed | : 1755 rpm | Noise level ² | : 60.0 dB(A) |
| Slip | : 2.50 % | Starting method | : Direct On Line |
| Rated torque | : 29.9 ft.lb | Approx. weight ³ | : 151 lb |
| Locked rotor torque | : 210 % | | |
| Breakdown torque | : 260 % | | |
| Insulation class | : F | | |
| Service factor | : 1.15 | | |
| Moment of inertia (J) | : 1.29 sq.ft.lb | | |
| Design | : B | | |

| | | | | | | |
|----------------|------|------|------|------|------------------|----------|
| Output | 25% | 50% | 75% | 100% | Foundation loads | |
| Efficiency (%) | 89.3 | 89.5 | 89.5 | 89.5 | Max. traction | : 363 lb |
| Power Factor | 0.45 | 0.72 | 0.82 | 0.87 | Max. compression | : 514 lb |

| | | | |
|----------------------|---|------------------|----------------------|
| | | <u>Drive end</u> | <u>Non drive end</u> |
| Bearing type | : | 6209 ZZ | 6206 ZZ |
| Sealing | : | V'Ring | Without Bearing Seal |
| Lubrication interval | : | - | - |
| Lubricant amount | : | - | - |
| Lubricant type | : | Mobil Polyrex EM | |

Notes:
USABLE @208V 26.8A SF 1.00 SFA 26.8A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

| Rev. | Changes Summary | Performed | Checked | Date |
|--------------|-----------------|---------------------------|---------|------|
| | | | | |
| Performed by | | Page 1 / 1 Revision | | |
| Checked by | | | | |
| Date | 29/03/2024 | | | |