DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer :

Product line	: Close Coupled Pump NEMA Premium Efficiency Three-Phase	Product code :	11084484
		Catalog # :	01036OT3H213JM

Frame	: 213/5JM	Locked rotor time	: 27s (cold) 15s (hot)
Output	: 10 HP (7.5 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 9.52 A	Protection degree	: IP21
L. R. Amperes	: 68.5 A	Cooling method	: IC01 - ODP
LRC	: 7.2x(Code H)	Mounting	: F-1
No load current	: 2.80 A	Rotation¹	: Both (CW and CCW)
Rated speed	: 3540 rpm	Noise level²	: 68.0 dB(A)
Slip	: 1.67 %	Starting method	: Direct On Line
Rated torque	: 14.8 ft.lb	Approx. weight³	: 128 lb
Locked rotor torque	: 220 %		
Breakdown torque	: 310 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.4881 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%
Efficiency (%)	89.3	89.5	90.2	90.2
Power Factor	0.50	0.73	0.83	0.88

Foundation loads	
Max. traction	: 195 lb
Max. compression	: 323 lb

		Drive end	Non drive end
Bearing type	:	6209 ZZ	6206 ZZ
Sealing	:	Without Bearing Seal	Without Bearing Seal
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	28/03/2024		1 / 1	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice