

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 Close Coupled Pump JM High Efficiency Three-Phase

Product code : 11641067

Frame : 213/5JM  
Output : 15 HP (11 kW)  
Poles : 2  
Frequency : 60 Hz  
Rated voltage : 575 V  
Rated current : 13.4 A  
L. R. Amperes : 84.7 A  
LRC : 6.3x(Code G)  
No load current : 3.36 A  
Rated speed : 3500 rpm  
Slip : 2.78 %  
Rated torque : 22.5 ft.lb  
Locked rotor torque : 200 %  
Breakdown torque : 250 %  
Insulation class : F  
Service factor : 1.15  
Moment of inertia (J) : 0.6402 sq.ft.lb  
Design : B

Locked rotor time : 27s (cold) 15s (hot)  
Temperature rise : 80 K  
Duty cycle : Cont.(S1)  
Ambient temperature : -20°C to +40°C  
Altitude : 1000 m.a.s.l.  
Protection degree : IP55  
Cooling method : IC411 - TEFC  
Mounting : F-1  
Rotation<sup>1</sup> : Both (CW and CCW)  
Noise level<sup>2</sup> : 72.0 dB(A)  
Starting method : Direct On Line  
Approx. weight<sup>3</sup> : 177 lb

Output	25%	50%	75%	100%
Efficiency (%)	89.2	89.5	90.2	90.2
Power Factor	0.61	0.84	0.89	0.91

Foundation loads  
Max. traction : 229 lb  
Max. compression : 405 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
10.5	8.6	7.7	4.7	2.9	1.7	1.0

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6309 Z C3	6207 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	19000 h	40000 h
Lubricant amount	:	13 g	0 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	29/03/2024			
		Revision		