

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel JP Pump NEMA Premium  
Efficiency Three-Phase

Product code : 12682730

Catalog # : 01018OT3V215JP-S

Frame : 213/5JP  
Output : 10 HP (7.5 kW)  
Poles : 4  
Frequency : 60 Hz  
Rated voltage : 200/400 V  
Rated current : 28.5/14.3 A  
L. R. Amperes : 200/100 A  
LRC : 7.0x(Code H)  
No load current : 13.8/6.89 A  
Rated speed : 1770 rpm  
Slip : 1.67 %  
Rated torque : 29.7 ft.lb  
Locked rotor torque : 250 %  
Breakdown torque : 350 %  
Insulation class : F  
Service factor : 1.15  
Moment of inertia (J) : 1.30 sq.ft.lb  
Design : B

Locked rotor time : 25s (cold) 14s (hot)  
Temperature rise : 80 K  
Duty cycle : Cont.(S1)  
Ambient temperature : -20°C to +40°C  
Altitude : 1000 m.a.s.l.  
Cooling method : IC01 - ODP  
Mounting : F-1  
Rotation<sup>1</sup> : Both (CW and CCW)  
Noise level<sup>2</sup> : 59.0 dB(A)  
Starting method : Direct On Line  
Approx. weight<sup>3</sup> : 133 lb

Output	25%	50%	75%	100%
Efficiency (%)	89.4	90.2	91.0	91.7
Power Factor	0.38	0.64	0.77	0.83

Efficiency (%)	89.4	90.2	91.0	91.7
Power Factor	0.38	0.64	0.77	0.83

Foundation loads

Max. traction : 519 lb  
Max. compression : 652 lb

	Drive end	Non drive end
Bearing type	6209 ZZ	6206 ZZ
Sealing	Without Bearing Seal	Without Bearing Seal
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	29/03/2024			

Page 1 / 1  
Revision