

Three Phase Induction Motor - Squirrel Cage



Product line : Close Coupled Pump High Efficiency Three-Phase Product code : 10804554

Frame	: 326JP	Locked rotor time	: 30s (cold) 17s (hot)
Output	: 60 HP (45 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 70.6 A	Protection degree	: IP23
L. R. Amperes	: 424 A	Cooling method	: IC01 - ODP
LRC	: 6.0x(Code G)	Mounting	: F-1
No load current	: 20.0 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 3555 rpm	Noise level ²	: 75.0 dB(A)
Slip	: 1.25 %	Starting method	: Direct On Line
Rated torque	: 88.6 ft.lb	Approx. weight ³	: 509 lb
Locked rotor torque	: 220 %		
Breakdown torque	: 210 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 3.94 sq.ft.lb		
Design	: B		

Output	25%		50%		75%		100%		Foundation loads	
Efficiency (%)	92.3	91.4	92.4	91.0	93.0	91.7	93.0	91.0	Max. traction	: 565 lb
	91.4	91.6	91.0	91.7	91.7	91.7	91.0	91.7		
Power Factor	0.53	0.62	0.77	0.83	0.84	0.86	0.86	0.87	Max. compression	: 1074 lb
	0.57	0.52	0.80	0.76	0.84	0.82	0.85	0.84		

	<u>Drive end</u>	<u>Non drive end</u>
Bearing type	6312 Z C3	6212 Z C3
Sealing	Without Bearing Seal	Without Bearing Seal
Lubrication interval	19658 h	20000 h
Lubricant amount	21 g	13 g
Lubricant type	Mobil Polyrex EM	

Notes:

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 1 / 1	Revision
Checked by					
Date	28/03/2024				