

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IE2 Three-Phase

Product code : 14421482
Catalog # : E11018EP3Y315SMF3-W2

Frame	: 315S/M	Locked rotor time	: 46s (cold) 26s (hot)
Output	: 110 kW (150 HP)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: S1
Frequency	: 50 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 380/660 V	Altitude	: 1000 m.a.s.l.
Rated current	: 205/118 A	Protection degree	: IP55
L. R. Amperes	: 1230/708 A	Cooling method	: IC411 - TEFC
LRC	: 6.0	Mounting	: B3T
No load current	: 54.0/31.1 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1487 rpm	Noise level ²	: 71.0 dB(A)
Slip	: 0.87 %	Starting method	: Direct On Line
Rated torque	: 521 ft.lb	Approx. weight ³	: 2045 lb
Locked rotor torque	: 180 %		
Breakdown torque	: 200 %		
Insulation class	: F		
Service factor	: 1.00		
Moment of inertia (J)	: 60.9 sq.ft.lb		
Design	: N		

Output	25%	50%	75%	100%	Foundation loads					
Efficiency (%)	94.5	94.2	94.6	94.3	94.9	95.0	Max. traction	: 1574 lb		
	93.6	92.4	93.9	93.0	94.8	94.5			95.0	95.0
Power Factor	0.56	0.50	0.78	0.74	0.85	0.83	0.86	0.86	Max. compression	: 3618 lb
	0.47	0.49	0.70	0.72	0.81	0.81	0.84	0.84		

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	5.2	5.1	5.1	5.1
	P2 (0,5;1,0)	4.0	3.9	3.9	3.9
	P3 (0,25;1,0)	3.5	3.4	3.4	3.4
	P4 (0,9;0,5)	2.7	2.7	2.7	2.7
	P5 (0,5;0,5)	1.6	1.6	1.6	1.6
	P6 (0,5;0,25)	1.1	1.1	1.1	1.1
	P7 (0,25;0,25)	0.6	0.6	0.6	0.6

		Drive end	Non drive end
Bearing type	:	6319 C3	6316 C3
Sealing	:	WSeal	WSeal
Lubrication interval	:	11000 h	13000 h
Lubricant amount	:	45 g	34 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	26/03/2024			
			Page	Revision
			1 / 2	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by					
Date	26/03/2024			2 / 2	