## DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



8 86.2 88.5 88.0 8 5 89.0 8	00% F	Product con Catalog # :  Locked rotor time Temperature rise Duty cycle Ambient temperatu Altitude Protection degree Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³	: 39s : 80 k : S1 ure : -20° : 100 : IP55 : IC4 : B3T : Both : 51.0	(cold) 22s (hot) (C to +40°C 0 m.a.s.l. 5 11 - TEFC (CW and CCW) 0 dB(A) ect On Line
10 HP (7.5 kW) 8 50 Hz 380 V 17.4 A 85.3 A 4.9 9.50 A 720 rpm 4.00 % 72.9 ft.lb 190 % 210 % F 1.25 3.75 sq.ft.lb N  75% 1 8 86.2 88.5 88.0 8 5 89.0 8		Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation <sup>1</sup> Noise level <sup>2</sup> Starting method Approx. weight <sup>3</sup>	: 80 k : S1 ure : -20° : 100 : IP55 : IC4 : B3T : Both : 51.0 : Dire	C to +40°C 0 m.a.s.l. 5 11 - TEFC 11 (CW and CCW) 0 dB(A) 11 ct On Line
10 HP (7.5 kW) 8 50 Hz 380 V 17.4 A 85.3 A 4.9 9.50 A 720 rpm 4.00 % 72.9 ft.lb 190 % 210 % F 1.25 3.75 sq.ft.lb N  75% 1 8 86.2 88.5 88.0 8 5 89.0 8		Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation <sup>1</sup> Noise level <sup>2</sup> Starting method Approx. weight <sup>3</sup>	: 80 k : S1 ure : -20° : 100 : IP55 : IC4 : B3T : Both : 51.0 : Dire	C to +40°C 0 m.a.s.l. 5 11 - TEFC 11 (CW and CCW) 0 dB(A) 11 ct On Line
8 50 Hz 380 V 17.4 A 85.3 A 4.9 9.50 A 720 rpm 4.00 % 72.9 ft.lb 190 % 210 % F 1.25 3.75 sq.ft.lb N  75% 1 8 86.2 88.5 88.0 8 5 89.0 8		Duty cycle Ambient temperate Altitude Protection degree Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³	: S1 ure : -20° : 100 : IP55 : IC4 : B3T : Bott : 51.0 : Dire	C to +40°C 0 m.a.s.l. 5 11 - TEFC (CW and CCW) 0 dB(A) ect On Line
50 Hz 380 V 17.4 A 85.3 A 4.9 9.50 A 720 rpm 4.00 % 72.9 ft.lb 190 % 210 % F 1.25 3.75 sq.ft.lb N  75% 1 8 86.2 88.5 88.0 8 5 89.0 8		Ambient temperate Altitude Protection degree Cooling method Mounting Rotation <sup>1</sup> Noise level <sup>2</sup> Starting method Approx. weight <sup>3</sup>	ure : -20° : 100 : IP55 : IC4 : B3T : Bott : 51.0 : Dire	0 m.a.s.l. 5 11 - TEFC n (CW and CCW) 0 dB(A) ect On Line
380 V 17.4 A 85.3 A 4.9 9.50 A 720 rpm 4.00 % 72.9 ft.lb 190 % 210 % F 1.25 3.75 sq.ft.lb N 75% 1 8 86.2 88.5 88.0 8 5 89.0 8		Altitude Protection degree Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³	: 100 : IP59 : IC4 : B3T : Bott : 51.0 : Dire	0 m.a.s.l. 5 11 - TEFC n (CW and CCW) 0 dB(A) ect On Line
17.4 A 85.3 A 4.9 9.50 A 720 rpm 4.00 % 72.9 ft.lb 190 % 210 % F 1.25 3.75 sq.ft.lb N 75% 1 8 86.2 88.5 88.0 8 5 89.0 8		Protection degree Cooling method Mounting Rotation <sup>1</sup> Noise level <sup>2</sup> Starting method Approx. weight <sup>3</sup>	: IP58 : IC4 : B3T : Bott : 51.0 : Dire	n (CW and CCW) Odb(A) oct On Line
85.3 A 4.9 9.50 A 720 rpm 4.00 % 72.9 ft.lb 190 % 210 % F 1.25 3.75 sq.ft.lb N  75% 1 8 86.2 88.5 88.0 8 5 89.0 8		Cooling method Mounting Rotation <sup>1</sup> Noise level <sup>2</sup> Starting method Approx. weight <sup>3</sup>	: IC4 : B3T : Bott : 51.0 : Dire	n (CW and CCW) Odb(A) oct On Line
4.9 9.50 A 720 rpm 4.00 % 72.9 ft.lb 190 % 210 % F 1.25 3.75 sq.ft.lb N  75% 1 8 86.2 88.5 88.0 8 5 89.0 8		Mounting Rotation <sup>1</sup> Noise level <sup>2</sup> Starting method Approx. weight <sup>3</sup>	: B3T : Both : 51.0 : Dire	n (CW and CCW) odB(A) oct On Line
9.50 A 720 rpm 4.00 % 72.9 ft.lb 190 % 210 % F 1.25 3.75 sq.ft.lb N  75% 1 8 86.2 88.5 88.0 8 5 89.0 8		Rotation <sup>1</sup> Noise level <sup>2</sup> Starting method Approx. weight <sup>3</sup>	: Both : 51.0 : Dire	n (CW and CCW) OdB(A) ect On Line
9.50 A 720 rpm 4.00 % 72.9 ft.lb 190 % 210 % F 1.25 3.75 sq.ft.lb N  75% 1 8 86.2 88.5 88.0 8 5 89.0 8		Rotation <sup>1</sup> Noise level <sup>2</sup> Starting method Approx. weight <sup>3</sup>	: 51.0 : Dire	) dB(A) ect On Line
720 rpm 4.00 % 72.9 ft.lb 190 % 210 % F 1.25 3.75 sq.ft.lb N 75% 1 8 86.2 88.5 88.0 8 5 89.0 8		Noise level <sup>2</sup> Starting method Approx. weight <sup>3</sup>	: 51.0 : Dire	) dB(A) ect On Line
4.00 % 72.9 ft.lb 190 % 210 % F 1.25 3.75 sq.ft.lb N  75% 1 8 86.2 88.5 88.0 8 5 89.0 8		Starting method Approx. weight <sup>3</sup>	: Dire	ct On Line
72.9 ft.lb 190 % 210 % F 1.25 3.75 sq.ft.lb N 75% 1 8 86.2 88.5 88.0 8 5 89.0 8		Approx. weight <sup>3</sup>		
190 % 210 % F 1.25 3.75 sq.ft.lb N 75% 1 8 86.2 88.5 88.0 8 5 89.0 8			. 309	iu
210 % F 1.25 3.75 sq.ft.lb N 75% 1 8 86.2 88.5 88.0 8 5 89.0 8				
F 1.25 3.75 sq.ft.lb N 75% 1 8 86.2 88.5 88.0 8 5 89.0 8				
1.25 3.75 sq.ft.lb N 75% 1 8 86.2 88.5 88.0 8 5 89.0 8				
3.75 sq.ft.lb N 75% 1 8 86.2 88.5 88.0 8 5 89.0 8				
N				
% 75% 1 8 86.2 88.5 88.0 8 5 89.0 8				
8 86.2 88.5 88.0 8 5 89.0 8		Coundation lands		
5 89.0 8	7 5 9 7 5 N	Foundation loads		
5 89.0 8		Max. traction	: 708 lb	)
	9.5			
6 N 10 N 69 N 61 N		Max. compression	: 1017	lh
6 0.49 0.68 0.61 0 9 0.62 0	.70	wax. compression	. 1017	ID
		tage of rated output		_
1,0) 13.		13.8	11.3	
1,0) 11.	.8	11.8	9.7	
1,0) 11.	.5	11.5	9.5	
),5) 8.	1	8.1	6.7	
	1	6.1	5.0	_
				<del>-</del>
				_
• ,			l .	
· · · · · · · · · · · · · · · · · · ·				
	•			
13 g			9 g	
	Mobil	l Polyrex EM		
1	,0) 11. ,5) 8. ,5) 6. 25) 4. ,25) 3. Drive en 6309 C V'Ring 20000	,0) 11.5 ,5) 8.1 ,5) 6.1 25) 4.8 ,25) 3.7 <u>Drive end</u> 6309 C3 V'Ring 20000 h 13 g	,0)     11.5       ,5)     8.1       ,5)     6.1       ,25)     4.8       ,25)     3.7       3.7     3.7       Non dri     6309 C3       V'Ring     V'I       20000 h     200	(0)     11.5     9.5       (5)     8.1     8.1     6.7       (5)     6.1     6.1     5.0       (25)     4.8     4.8     4.0       (25)     3.7     3.7     3.1       3.7     3.7     3.1       5.0     0.0     0.0     0.0       6309 C3     0.0     0.0     0.0       7.0     0.0     0.0     0.0     0.0       8     0.0     0.0     0.0     0.0     0.0     0.0       9     0.0

(+) At 100 / 01 full load.						
Rev.	Changes Summary			Performed	Checked	Date
Performed by						
Checked by					Page	Revision
Date	26/03/2024	1			1/1	