

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22Xec IE3 Three-Phase

Product code : 13056480

Area classification : ZONA 2/22, GRUPO IIC/IIIB, T3(200 °C)/
T125 °C

Catalog # : E11036ET3YAX315SMF3W

Frame : 315S/M
Output : 110 kW (150 HP)
Poles : 2
Frequency : 50 Hz
Rated voltage : 380/660 V
Rated current : 199/115 A
L. R. Amperes : 1294/745 A
LRC : 6.5
No load current : 54.0/31.1 A
Rated speed : 2975 rpm
Slip : 0.83 %
Rated torque : 261 ft.lb
Locked rotor torque : 160 %
Breakdown torque : 250 %
Insulation class : F
Service factor : 1.00
Moment of inertia (J) : 39.5 sq.ft.lb
Design : N

Locked rotor time : 93s (cold) 52s (hot)
Temperature rise : 80 K
Duty cycle : S1
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : B3T
Rotation¹ : Both (CW and CCW)
Noise level² : 77.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 2025 lb

Output	25%		50%		75%		100%	
Efficiency (%)	94.5	94.1	94.6	94.3	95.4	95.3	95.4	95.4
	93.8	92.1	94.1	92.8	95.2	94.4	95.4	95.0
Power Factor	0.57	0.53	0.81	0.78	0.86	0.85	0.88	0.87
	0.50	0.51	0.75	0.76	0.83	0.84	0.86	0.87

Foundation loads
Max. traction : 649 lb
Max. compression : 2674 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	4.5	4.5	4.5	4.9
	P2 (0,5;1,0)	3.2	3.2	3.2	3.5
	P3 (0,25;1,0)	2.8	2.8	2.8	3.0
	P4 (0,9;0,5)	2.6	2.6	2.6	2.9
	P5 (0,5;0,5)	1.4	1.4	1.4	1.5
	P6 (0,5;0,25)	1.0	1.0	1.0	1.1
	P7 (0,25;0,25)	0.5	0.5	0.5	0.6

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6314 C3	6314 C3
Sealing	:	WSeal	WSeal
Lubrication interval	:	5000 h	5000 h
Lubricant amount	:	27 g	27 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

ATEX
Baseefa 10ATEX0192X
BAS21UKEX0284X
II 3G Ex ec IIC T3 Gc
II 3D Ex tc IIIB T125°C Dc
EAC
TC RU C-BR.AA87.B.00977/22
2Ex ec IIC T3 Gc X
Ex tc IIIB T125°C Dc X
ООО «НАИО ЛЦБЭ»
IECEX
IECEX BAS 10.0099X

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	27/03/2024			

Page 1 / 3
Revision

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Ex ec IIC T3 Gc
Ex tc IIIB T125°C Dc

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 3	Revision
Checked by					
Date	27/03/2024				

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	140 °C
2	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 3 / 3	Revision
Checked by					
Date	27/03/2024				