DATA SHEET



Three Phase Induction Motor - Squirrel Cage Customer Product line : W22 Tru-Metric IE2 Three-Phase Product code: 13025517 Frame : 54s (cold) 30s (hot) : 200L Locked rotor time Output : 20 HP (15 kW) Temperature rise : 80 K Poles Duty cycle : 8 : S1 Frequency : 50 Hz Ambient temperature : -20°C to +40°C Rated voltage : 380 V Altitude : 1000 m.a.s.l. Rated current : 32.7 A Protection degree : IP55 Cooling method : IC411 - TEFC L. R. Amperes : 160 A **LRC** : 4.9 Mounting : B3L(E) : Both (CW and CCW) No load current : 14.6 A Rotation¹ Rated speed : 725 rpm Noise level² : 56.0 dB(A) Slip : 3.33 % Starting method : Direct On Line Rated torque : 145 ft.lb Approx. weight3 : 536 lb Locked rotor torque : 170 % Breakdown torque : 180 % Insulation class : F Service factor : 1.15 Moment of inertia (J) : 10.0 sq.ft.lb Design : N Output 50% 75% 100% Foundation loads Efficiency (%) 90.5 89.4 90.4 90.4 89.4 90.2 Max. traction : 783 lb 90.2 91.0 91.0 Power Factor 0.62 0.55 0.73 0.67 0.78 0.74 Max. compression : 1320 lb 0.55 0.68 0.74 Losses at normative operating points (speed;torque), in percentage of rated output power P1 (0,9;1,0) 11.4 10.5 9.5 P2 (0,5;1,0) 9.6 8.8 8.0 P3 (0,25;1,0) 9.1 8.4 7.6 Losses (%) P4 (0,9;0,5) 6.1 5.6 5.1 P5 (0,5;0,5) 4.4 4.0 3.6 P6 (0,5;0,25) 3.2 2.9 2.7 P7 (0,25;0,25) 2.3 2.1 2.0 Drive end Non drive end Bearing type 6312 C3 6212 C3 V'Ring Sealing V'Ring Lubrication interval 20000 h 20000 h Lubricant amount 21 g 13 g Lubricant type Mobil Polyrex EM Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	26/03/2024			1/1	