

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W60 Hazardous Area Three-Phase

Product code :

16856004

Catalog # :

225036WT3X6810-
W60MV2

Frame : 6810/11
 Output : 2000 HP (1500 kW)
 Poles : 2
 Frequency : 60 Hz
 Rated voltage : 2300/4000 V
 Rated current : 447/257 A
 L. R. Amperes : 2906/1671 A
 LRC : 6.5x(Code G)
 No load current : 98.0/56.4 A
 Rated speed : 3573 rpm
 Slip : 0.75 %
 Rated torque : 2940 ft.lb
 Locked rotor torque : 45 %
 Breakdown torque : 229 %
 Insulation class : F
 Service factor : 1.15
 Moment of inertia (J) : 252 sq.ft.lb

Locked rotor time : 18s (cold) 10s (hot)
 Temperature rise : 80 K
 Duty cycle : Cont.(S1)
 Ambient temperature : 0°C to +40°C
 Altitude : 1000 m.a.s.l.
 Protection degree : IP24
 Mounting : F-1
 Rotation¹ : CCW
 Noise level² : 88.0 dB(A)
 Starting method : VFD

Output	25%	50%	75%	100%			
Efficiency (%)	0.000	95.0	95.4	95.8	95.8	95.8	95.8
Power Factor	0.00	0.00	0.82	0.82	0.87	0.87	0.88

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page		Revision
Checked by		1 /		
Date	27/03/2024			