

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W60 Hazardous Area Three-Phase

Product code : 16854231
Catalog # : 40036WT3X5010-W60MV1

Frame : 5010/11
Output : 300 HP (220 kW)
Poles : 2
Frequency : 60 Hz
Rated voltage : 2300/4000 V
Rated current : 68.8/39.5 A
L. R. Amperes : 516/296 A
LRC : 7.5x(Code H)
No load current : 24.0/13.8 A
Rated speed : 3577 rpm
Slip : 0.64 %
Rated torque : 440 ft.lb
Locked rotor torque : 80 %
Breakdown torque : 250 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 60.3 sq.ft.lb

Locked rotor time : 18s (cold) 10s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : 0°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP24
Mounting : F-1
Rotation¹ : CW
Noise level² : 85.0 dB(A)
Starting method : VFD

Output	25%	50%	75%	100%
Efficiency (%)	0.000	92.4	93.0	93.0 94.5 94.5 94.5
Power Factor	0.00	0.00	0.74	0.78 0.82 0.85 0.85 0.86

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / Revision		
Checked by				
Date	27/03/2024			