

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22Xdb IE2 Three-Phase

Product code : 13485816

Catalog # : E00518XP3YAX132SF3-W

Area classification : ZONA 1, GRUPO IIB, T4 (135 °C)

Frame	: 132S/M	Locked rotor time	: 18s (cold) 10s (hot)
Output	: 5.5 kW (7.5 HP)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: S1
Frequency	: 50 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 380/660 V	Altitude	: 1000 m.a.s.l.
Rated current	: 10.8/6.22 A	Protection degree	: IP56
L. R. Amperes	: 78.8/45.4 A	Cooling method	: IC411 - TEFC
LRC	: 7.3	Mounting	: B3T
No load current	: 4.70/2.71 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 1460 rpm	Noise level ²	: 56.0 dB(A)
Slip	: 2.67 %	Starting method	: Direct On Line
Rated torque	: 26.5 ft.lb	Approx. weight ³	: 231 lb
Locked rotor torque	: 170 %		
Breakdown torque	: 270 %		
Insulation class	: F		
Service factor	: 1.00		
Moment of inertia (J)	: 1.25 sq.ft.lb		
Design	: N		

Output	25%	50%	75%	100%	Foundation loads					
Efficiency (%)	87.9	85.9	88.1	86.5	87.7	87.3	87.7	87.7	Max. traction	: 304 lb
	85.9	85.3	86.5	86.8	87.3	88.0	87.7	89.5		
Power Factor	0.45	0.41	0.73	0.68	0.83	0.80	0.88	0.86	Max. compression	: 535 lb
	0.38	0.38	0.65	0.63	0.77	0.76	0.84	0.83		

					<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:				6308 ZZ	6207 ZZ
Sealing	:				Oil Seal	Lip Seal
Lubrication interval	:				-	-
Lubricant amount	:				-	-
Lubricant type	:				Mobil Polyrex EM	

Notes:

EAC
EA3C RU C-BR.AA87.B.00379/20
1Ex db IIB T4 Gb X
ООО «НАННО ЦСВЭ»
IECEX
IECEX INE 22.0044X
Ex db IIB T4 Gb

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	27/03/2024			
			Page	Revision
			1 / 2	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	150 °C

Space heater information

Voltage: 200 - 240 V

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by					
Date	27/03/2024			2 / 2	