

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22Xdb IE3 Three-Phase

Product code : 12430972

Area classification : ZONA 1, GRUPO IIB, T4 (135 °C)

Catalog # : E05536XT3YAX250SMF3W

Frame : 250S/M
Output : 55 kW (75 HP)
Poles : 2
Frequency : 50 Hz
Rated voltage : 380/660 V
Rated current : 101/58.2 A
L. R. Amperes : 758/436 A
LRC : 7.5
No load current : 31.0/17.8 A
Rated speed : 2960 rpm
Slip : 1.33 %
Rated torque : 131 ft.lb
Locked rotor torque : 240 %
Breakdown torque : 290 %
Insulation class : F
Service factor : 1.00
Moment of inertia (J) : 8.86 sq.ft.lb
Design : N

Locked rotor time : 16s (cold) 9s (hot)
Temperature rise : 80 K
Duty cycle : S1
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP56
Cooling method : IC411 - TEFC
Mounting : B3T
Rotation¹ : Both (CW and CCW)
Noise level² : 74.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 1332 lb

Output	25%		50%		75%		100%	
Efficiency (%)	93.1	92.8	93.5	93.3	94.0	94.0	94.3	94.4
	92.6	92.0	93.1	92.2	94.0	93.6	94.4	93.6
Power Factor	0.54	0.49	0.79	0.75	0.85	0.83	0.88	0.86
	0.46	0.47	0.72	0.73	0.81	0.82	0.85	0.86

Foundation loads
Max. traction : 544 lb
Max. compression : 1867 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	5.7	5.5	5.5	6.4
	P2 (0,5;1,0)	4.3	4.2	4.2	4.9
	P3 (0,25;1,0)	4.0	3.9	3.9	4.5
	P4 (0,9;0,5)	2.9	2.9	2.9	3.3
	P5 (0,5;0,5)	1.7	1.7	1.7	1.9
	P6 (0,5;0,25)	1.1	1.1	1.1	1.3
	P7 (0,25;0,25)	0.7	0.6	0.6	0.7

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6314 C3	6314 C3
Sealing	:	Viton Oil Seal	Viton Oil Seal
Lubrication interval	:	5000 h	5000 h
Lubricant amount	:	27 g	27 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

ATEX
INERIS 17ATEX0001X
CML 21UKEX1314X
II 2G Ex db IIB T4 Gb
EAC
EAЭC RU C-BR.AA87.B.00379/20
1Ex db IIB T4 Gb X
ООО «НАННО ЦСВЭ»
IECEX
IECEX INE 16.0060X
Ex db IIB T4 Gb

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 3		
Checked by				
Date	27/03/2024			
		Revision		

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 2 / 3		Revision
Checked by					
Date	27/03/2024				

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	150 °C

Space heater information

Voltage: 200 - 240 V

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 3 / 3	Revision
Checked by					
Date	27/03/2024				