

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IE2 Three-Phase

Product code : 14427590  
Catalog # : E13212EP3Y315SMF3-W2

Frame	: 315S/M	Locked rotor time	: 30s (cold) 17s (hot)
Output	: 132 kW (175 HP)	Temperature rise	: 80 K
Poles	: 6	Duty cycle	: S1
Frequency	: 50 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 380/660 V	Altitude	: 1000 m.a.s.l.
Rated current	: 249/143 A	Protection degree	: IP55
L. R. Amperes	: 1594/918 A	Cooling method	: IC411 - TEFC
LRC	: 6.4	Mounting	: B3T
No load current	: 87.1/50.1 A	Rotation <sup>1</sup>	: Both (CW and CCW)
Rated speed	: 990 rpm	Noise level <sup>2</sup>	: 67.0 dB(A)
Slip	: 1.00 %	Starting method	: Direct On Line
Rated torque	: 940 ft.lb	Approx. weight <sup>3</sup>	: 2284 lb
Locked rotor torque	: 200 %		
Breakdown torque	: 210 %		
Insulation class	: F		
Service factor	: 1.00		
Moment of inertia (J)	: 151 sq.ft.lb		
Design	: N		

Output	25%	50%	75%	100%	Foundation loads					
Efficiency (%)	95.0	94.5	94.9	94.6	95.0	95.0	94.8	95.0	Max. traction	: 3734 lb
	94.1	94.0	94.3	94.1	94.9	95.0	95.0	95.0		
Power Factor	0.49	0.44	0.75	0.71	0.83	0.80	0.85	0.84	Max. compression	: 6019 lb
	0.41	0.42	0.68	0.67	0.78	0.80	0.83	0.84		

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	5.4	5.2	5.2	5.2
	P2 (0,5;1,0)	4.4	4.2	4.2	4.2
	P3 (0,25;1,0)	4.0	3.9	3.9	3.9
	P4 (0,9;0,5)	2.6	2.5	2.5	2.5
	P5 (0,5;0,5)	1.8	1.7	1.7	1.7
	P6 (0,5;0,25)	1.2	1.1	1.1	1.1
	P7 (0,25;0,25)	0.7	0.7	0.7	0.7

		Drive end	Non drive end
Bearing type	:	6319 C3	6316 C3
Sealing	:	WSeal	WSeal
Lubrication interval	:	16000 h	18000 h
Lubricant amount	:	45 g	34 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	26/03/2024			
			Page	Revision
			1 / 2	

Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date	26/03/2024				