DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer Product line : W22 Tru-Metric IE3 Three-Phase Product code: 11701287 Catalog #: 00418ET3Y112M-W22 Frame : 112M Locked rotor time : 27s (cold) 15s (hot) Output : 5.5 HP (4 kW) Temperature rise : 80 K Poles : 4 Duty cycle : S1 Frequency : 50 Hz Ambient temperature : -20°C to +40°C Rated voltage : 380 V Altitude : 1000 m.a.s.l. Rated current : 8.47 A Protection degree : IP55 : IC411 - TEFC L. R. Amperes : 59.3 A Cooling method Mounting **LRC** : 7.0 : B3L(E) : Both (CW and CCW) No load current : 4.15 A Rotation¹ Rated speed : 1445 rpm Noise level² : 56.0 dB(A) Slip : 3.67 % Starting method : Direct On Line Rated torque : 20.0 ft.lb Approx. weight³ : 96.8 lb Locked rotor torque : 200 % Breakdown torque : 270 % Insulation class : F Service factor : 1.25 Moment of inertia (J) : 0.4312 sq.ft.lb Design : N 75% 100% Output 50% Foundation loads Efficiency (%) 89.3 88.2 89.0 88.9 88.6 89.3 Max. traction : 321 lb 87.5 89.5 89.5 Power Factor 0.65 0.57 0.76 0.70 0.81 0.77 Max. compression : 417 lb 0.58 0.70 0.77 Losses at normative operating points (speed;torque), in percentage of rated output power P1 (0,9;1,0) 12.3 11.4 11.2 P2 (0,5;1,0) 10.3 9.6 9.4 P3 (0,25;1,0) 10.0 9.3 9.2 Losses (%) P4 (0,9;0,5) 6.9 6.4 6.3 P5 (0,5;0,5) 5.0 4.6 4.5 P6 (0,5;0,25) 3.8 3.5 3.4 P7 (0,25;0,25) 2.8 2.6 2.6 Non drive end **Drive end** 6206 ZZ Bearing type 6207 ZZ V'Ring V'Ring Sealing Lubrication interval Lubricant amount Lubricant type Mobil Polyrex EM Notes: This revision replaces and cancel the previous one, which These are average values based on tests with sinusoidal must be eliminated. power supply, subject to the tolerances stipulated in NEMA (1) Looking the motor from the shaft end. MG-1. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load. Rev. **Changes Summary** Performed Checked Date Performed by Checked by Page Revision

1/1

26/03/2024

Date