

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22Xec IE3 Three-Phase

Product code : 12861531

Area classification : ZONA 2/22, GRUPO IIC/IIIB, T3(200 °C)/
T125 °C

Catalog # : E01512ET3YAX180LF3-W

Frame : 180L
Output : 15 kW (20 HP)
Poles : 6
Frequency : 50 Hz
Rated voltage : 380/660 V
Rated current : 30.1/17.3 A
L. R. Amperes : 232/133 A
LRC : 7.7
No load current : 16.0/9.21 A
Rated speed : 975 rpm
Slip : 2.50 %
Rated torque : 108 ft.lb
Locked rotor torque : 290 %
Breakdown torque : 320 %
Insulation class : F
Service factor : 1.00
Moment of inertia (J) : 7.05 sq.ft.lb
Design : N

Locked rotor time : 14s (cold) 8s (hot)
Temperature rise : 80 K
Duty cycle : S1
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : B3T
Rotation¹ : Both (CW and CCW)
Noise level² : 56.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 397 lb

Output	50%	75%	100%
Efficiency (%)	90.7 90.0	91.0 91.2	91.2 91.2
	89.0 90.5	91.0 91.7	91.2 91.7
Power Factor	0.65 0.61	0.76 0.73	0.83 0.80
	0.57 0.59	0.70 0.71	0.78 0.79

Foundation loads
Max. traction : 1517 lb
Max. compression : 1917 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	9.5	9.5	9.5	8.9
	P2 (0,5;1,0)	8.6	8.6	8.6	8.1
	P3 (0,25;1,0)	8.5	8.5	8.5	7.9
	P4 (0,9;0,5)	4.5	4.5	4.5	4.3
	P5 (0,5;0,5)	3.5	3.5	3.5	3.2
	P6 (0,5;0,25)	2.4	2.4	2.4	2.2
	P7 (0,25;0,25)	1.8	1.8	1.8	1.7

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6311 C3	6211 C3
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	20000 h	20000 h
Lubricant amount	:	18 g	11 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

ATEX
Baseefa 10ATEX0192X
BAS21UKEX0284X
II 3G Ex ec IIC T3 Gc
II 3D Ex tc IIIB T125°C Dc
EAC
TC RU C-BR.AA87.B.00977/22
2Ex ec IIC T3 Gc X
Ex tc IIIB T125°C Dc X
OOO «НАННО ЦСБЭ»
IECEX
IECEX BAS 10.0099X

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 3 Revision		
Checked by				
Date	27/03/2024			

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Ex ec IIC T3 Gc
Ex tc IIIB T125°C Dc

Rev.	Changes Summary		Performed	Checked	Date
Performed by			Page 2 / 3		Revision
Checked by					
Date	27/03/2024				

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	140 °C
2	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 3 / 3	Revision
Checked by					
Date	27/03/2024				