

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22Xdb IE2 Three-Phase

Product code : 12383753

Catalog # : E11036XP3YAX315SMF3W

Area classification : ZONA 1, GRUPO IIB, T4 (135 °C)

Frame	: 315S/M	Locked rotor time	: 43s (cold) 24s (hot)
Output	: 110 kW (150 HP)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: S1
Frequency	: 50 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 380/660 V	Altitude	: 1000 m.a.s.l.
Rated current	: 200/115 A	Protection degree	: IP56
L. R. Amperes	: 1400/806 A	Cooling method	: IC411 - TEFC
LRC	: 7.0	Mounting	: B3T
No load current	: 51.0/29.4 A	Rotation ¹	: Both (CW and CCW)
Rated speed	: 2977 rpm	Noise level ²	: 77.0 dB(A)
Slip	: 0.77 %	Starting method	: Direct On Line
Rated torque	: 260 ft.lb	Approx. weight ³	: 2443 lb
Locked rotor torque	: 180 %		
Breakdown torque	: 270 %		
Insulation class	: F		
Service factor	: 1.00		
Moment of inertia (J)	: 39.6 sq.ft.lb		
Design	: N		

Output	25%		50%		75%		100%		Foundation loads	
Efficiency (%)	94.5	94.2	94.5	94.3	94.9	94.9	94.8	94.9	Max. traction	: 492 lb
	93.9	91.9	94.1	92.4	94.8	94.1	94.9	94.5		
Power Factor	0.58	0.53	0.81	0.77	0.87	0.85	0.88	0.87	Max. compression	: 2935 lb
	0.50	0.52	0.74	0.76	0.83	0.84	0.86	0.87		

					<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:				6314 C3	6314 C3
Sealing	:				Viton Oil Seal	Viton Oil Seal
Lubrication interval	:				5000 h	5000 h
Lubricant amount	:				27 g	27 g
Lubricant type	:				Mobil Polyrex EM	

Notes:

EAC
EA3C RU C-BR.AA87.B.00379/20
1Ex db IIB T4 Gb X
ООО «НАННО ЦСВЭ»
IECEX
IECEX INE 16.0044X
Ex db IIB T4 Gb

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by				
Date	27/03/2024			
			Page	Revision
			1 / 2	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	150 °C

Space heater information

Voltage: 200 - 240 V

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date	27/03/2024				