DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer Product line : W21 Explosion Proof High Efficiency Three-Product code: 11124467 : 504/5TS Locked rotor time Frame : 61s (cold) 34s (hot) Output : 250 HP (185 kW) Temperature rise : 80 K Poles Duty cycle : Cont.(S1) Frequency : 60 Hz Ambient temperature : -20°C to +40°C Rated voltage : 460 V Altitude : 1000 m.a.s.l. Rated current : 267 A Protection degree : IP55 : IC411 - TEFC L. R. Amperes : 1762 A Cooling method **LRC** : 6.6x(Code G) Mounting : F-1 : Both (CW and CCW) No load current : 50.0 A Rotation¹ Rated speed : 3570 rpm Noise level² : 88.0 dB(A) Slip : 0.83 % Starting method : Direct On Line Rated torque : 368 ft.lb Approx. weight³ : 2772 lb Locked rotor torque : 200 % Breakdown torque : 250 % : F Insulation class Service factor : 1.15 Moment of inertia (J) : 51.4 sq.ft.lb Design : B 25% 50% 75% 100% Output Foundation loads Efficiency (%) 93.4 93.6 95.4 95.4 Max. traction : 819 lb 0.91 Power Factor 0.68 0.88 0.90 Max. compression : 3592 lb Drive end Non drive end Bearing type 6316 C3 6316 C3 Oil Seal Lip Seal Sealing 4288 h Lubrication interval 4288 h Lubricant amount 34 g 34 g Lubricant type Isoflex NBU-15

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	27/03/2024			1/2	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



_	
Customer	
Custoffici	

Thermal protection

		•		
ID	Application	Туре	Quantity	Sensing Temperature
1	Winding	Thermostat - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary Performed		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	27/03/2024			2/2	