

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Saw Arbor Motor Standard Efficiency Three-Phase
Product code : 13574405
Catalog # : 00718ES3ESA90LR

Frame	: 90L/MS	Locked rotor time	: 12s (cold) 7s (hot)
Output	: 7.5 HP (5.5 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: S6
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 208-230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 22.4-20.3/10.1 A	Protection degree	: IP54
L. R. Amperes	: 184-166/83.1 A	Cooling method	: IC411 - TEFC
LRC	: 8.2	Mounting	: B3R(D)
No load current	: 8.66-10.0/5.02 A	Rotation ¹	: CCW
Rated speed	: 1730 rpm	Noise level ²	: 55.0 dB(A)
Slip	: 3.89 %	Starting method	: Direct On Line
Rated torque	: 22.8 ft.lb	Approx. weight ³	: 165 lb
Locked rotor torque	: 370 %		
Breakdown torque	: 400 %		
Insulation class	: F		
Service factor	: 1.00		
Moment of inertia (J)	: 0.3322 sq.ft.lb		
Design	: N		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	0.000	83.5	85.0	85.3	Max. traction	: 611 lb
Power Factor	0.00	0.60	0.74	0.80	Max. compression	: 776 lb

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6308 ZZ	6208 ZZ
Sealing	:	Without Bearing Seal	Without Bearing Seal
Lubrication interval	:	0 h	0 h
Lubricant amount	:	0 g	0 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1 Revision		
Checked by				
Date	27/03/2024			