DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W60 Three-Phase Product code : 16166691

Frame : 5010/11 Locked rotor time : 21s (cold) 12s (hot)

Output : 1000 HP (750 kW) Temperature rise : 80 K
Poles : 2 Duty cycle : Cont.(S1)
Frequency : 60 Hz Ambient temperature : -20°C to +40°C

Frequency : 60 Hz Ambient temperature : -20°C to +40°C Rated voltage : 4160 V Altitude : 1000 m.a.s.l.

Rated current : 124 A Protection degree : IP24

L. R. Amperes : 781 A Mounting : F-1

Rotation¹ LRC : 6.3x(Code G) : CW : 80.0 dB(A) No load current : 26.0 A Noise level² Rated speed : 3558 rpm Starting method : Direct On Line Slip : 1.17 % Approx. weight3 : 4666 lb

Slip : 1.17 % Approx. weight³ : 4666 lb

Rated torque : 1480 ft.lb

Locked rotor torque : 80 %

Breakdown torque : 210 %

Insulation class : F

 Moment of inertia (J)
 : 93.9 sq.ft.lb

 Output
 25%
 50%
 75%
 100%
 Foundation loads

 Efficiency (%)
 94.4
 94.6
 95.6
 95.6
 Max. traction

Efficiency (%) 94.4 94.6 95.6 95.6 Max. traction

Power Factor 0.62 0.84 0.86 0.88 Max. compression

Drive end Non drive end

Bearing type : 6218 C4 6218 C4
Sealing : Without Bearing Seal Without Bearing Seal

Lubrication interval : 12045 h 12045 h Lubricant amount : 24 g 24 g

Lubricant type : Mobil Polyrex EM

: 1.00

Notes:

Service factor

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.

(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	27/03/2024			1/2	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer	

Thermal protection

ID	Application	Туре	Quantity	Sensing Temperature
1	Winding	PT100 - 3 wires	2 x Phase	-
2	DE bearing	PT100 - 3 wires	1 x Bearing	-
3	NDE bearing	PT100 - 3 wires	1 x Bearing	-

Space heater information

Voltage: 110-127/200-240 V

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	27/03/2024			2/2	