DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W60 Three-Phase Product code : 16166670

Frame : 5010/11 Locked rotor time : 34s (cold) 19s (hot)

Output : 550 HP (400 kW) Temperature rise : 80 K
Poles : 2 Duty cycle : Cont.(S1)

Frequency : 60 Hz Ambient temperature : -20°C to +40°C Rated voltage : 4160 V Altitude : 1000 m.a.s.l. Rated current : 66.3 A Protection degree : IP24

: F-1 : 431 A Mounting L. R. Amperes Rotation¹ **LRC** : 6.5x(Code G) : CW No load current : 15.4 A Noise level² : 80.0 dB(A) Rated speed : 3563 rpm Starting method : Direct On Line

Slip : 1.03 % Approx. weight³ : 4092 lb

Rated torque : 811 ft.lb

Locked rotor torque : 80 %

Breakdown torque : 220 %

 Moment of inertia (J)
 : 61.7 sq.ft.lb

 Output
 25%
 50%
 75%
 100%

 Efficiency (%)
 93.9
 94.1
 95.1
 95.1

 Max. traction

Efficiency (%) 93.9 94.1 95.1 95.1 Max. traction
Power Factor 0.61 0.84 0.86 0.88 Max. compression

Drive end Non dri

: F : 1.00

Lubrication interval : 12045 h Lubricant amount : 24 g 24 g

Lubricant type : Mobil Polyrex EM

Notes:

Insulation class

Service factor

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.

(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	27/03/2024			1/2	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer	

Thermal	protection
---------	------------

ID	Application	Туре	Quantity	Sensing Temperature
1	Winding	PT100 - 3 wires	2 x Phase	-
2	DE bearing	PT100 - 3 wires	1 x Bearing	-
3	NDE bearing	PT100 - 3 wires	1 x Bearing	-

Space heater information

Voltage: 110-127/200-240 V

Rev.	Changes Summary Performed		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	27/03/2024			2/2	