## DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer	:	· ·					
Product line	: Multimounting IE3 Three-Phase		Product code : Catalog # :		13984015 00218ET3WAL100L-W22		
Breakdown torqu Insulation class Service factor Moment of inertia	utput       : 3 HP (2.2 kW)         bles       : 4         equency       : 50 Hz         ated voltage       : 220/380 V         ated current       : 8.43/4.88 A         R. Amperes       : 62.4/36.1 A         RC       : 7.4         o load current       : 3.80/2.20 A         ated speed       : 1425 rpm         ip       : 5.00 %         ated torque       : 11.1 ft.lb         ocked rotor torque       : 280 %         reakdown torque       : 270 %         sulation class       : F		Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Protection degree Cooling method Mounting Rotation¹ Noise level² Starting method Approx. weight³		: 39s (cold) 22s (hot) : 80 K : S1 : -20°C to +40°C : 1000 m.a.s.l. : IP55 : IC411 - TEFC : B3L(E) : Both (CW and CCW) : 53.0 dB(A) : Direct On Line : 61.1 lb		
Design Output	: N 25% 50%	75% 100%	Foundation	on loads			
Efficiency (%)	87.2 85.0 87.2 85.7		Max. trac	tion	: 223 lb		
Power Factor	0.35 0.30 0.57 0.49	88.2 89.5 0.70 0.63 0.79 0.72 0.67 0.75	Max. con	npression	: 285 lb		
Losses at normati	ve operating points (sp	eed;torque), in perce	ntage of ra	ited output power			
	P1 (0,9;1,0) P2 (0,5;1,0) P3 (0,25;1,0)	14.4 11.6 11.1 8.2	1:	3.8 1.1 0.7	11.0 8.9 8.5		
Losses (%)	P4 (0,9;0,5) P5 (0,5;0,5) P6 (0,5;0,25) P7 (0,25;0,25)	5.5 4.1 3.0	5	7.9 5.3 1.0 2.8	6.3 4.2 3.2 2.3		
Bearing type Sealing Lubrication interv Lubricant amount Lubricant type		Drive end 6206 ZZ V'Ring - -	oil Polyrex	Non drive end 6205 ZZ V'Ring - -	<u>d</u>		
Notes:			•				
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.				
Rev.	Chang	ges Summary	1	Performed	Checked	Date	

Changes Summary		Performed	Checked	Date
			Page	Revision
26/03/2024			1/1	
				Page