

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W40 JP Pump NEMA Premium Efficiency
Three-Phase

Product code : 14836794

Catalog # : 06018OT3E364JPV-W40

Frame : 364/5JP
Output : 60 HP (45 kW)
Poles : 4
Frequency : 60 Hz
Rated voltage : 230/460 V
Rated current : 140/69.9 A
L. R. Amperes : 909/454 A
LRC : 6.5x(Code G)
No load current : 49.4/24.7 A
Rated speed : 1780 rpm
Slip : 1.11 %
Rated torque : 177 ft.lb
Locked rotor torque : 200 %
Breakdown torque : 240 %
Insulation class : F
Service factor : 1.25
Moment of inertia (J) : 15.6 sq.ft.lb
Design : B

Locked rotor time : 34s (cold) 19s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP23
Cooling method : IC01 - ODP
Mounting : W-6
Rotation¹ : Both (CW and CCW)
Noise level² : 69.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 754 lb

Output	25%	50%	75%	100%				
Efficiency (%)	94.4	93.4	94.5	93.5	95.0	93.9	95.0	93.9
Power Factor	0.48	0.49	0.73	0.74	0.82	0.83	0.85	0.86
	0.45	0.42	0.71	0.68	0.81	0.79	0.85	0.84

Foundation loads
Max. traction : 1259 lb
Max. compression : 2013 lb

	Drive end	Non drive end
Bearing type	6314 C3	6212 Z C3
Sealing	Without Bearing Seal	Without Bearing Seal
Lubrication interval	19579 h	20000 h
Lubricant amount	27 g	13 g
Lubricant type	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	30/03/2024			
		Revision		