DATA SHEET



Three Phase Induction Motor - Squirrel Cage Customer Product line : W22 Tru-Metric IE2 Three-Phase Product code: 12659159 Frame : 315L : 25s (cold) 14s (hot) Locked rotor time Output : 300 HP (220 kW) Temperature rise : 80 K Poles : 4 Duty cycle : S1 Frequency : 50 Hz Ambient temperature : -20°C to +40°C Rated voltage : 380 V Altitude : 1000 m.a.s.l. Rated current : 397 A Protection degree : IP55 Cooling method : IC411 - TEFC L. R. Amperes : 2779 A LRC : 7.0 Mounting : B3L(E) : Both (CW and CCW) No load current : 119 A Rotation¹ Rated speed : 1490 rpm Noise level² : 74.0 dB(A) Slip : 0.67 % Starting method : Direct On Line Rated torque : 1060 ft.lb Approx. weight3 : 3042 lb Locked rotor torque : 229 % Breakdown torque : 210 % Insulation class : F Service factor : 1.15 Moment of inertia (J) : 163 sq.ft.lb Design : N Output 50% 75% 100% Foundation loads Efficiency (%) 95.4 95.0 95.7 95.6 95.6 95.7 Max. traction : 4180 lb 94.5 95.4 95.4 Power Factor 0.80 0.73 0.86 0.82 0.88 0.86 Max. compression : 7222 lb 0.73 0.84 0.87 Losses at normative operating points (speed;torque), in percentage of rated output power P1 (0,9;1,0) 5.0 4.9 5.2 P2 (0,5;1,0) 3.4 3.3 3.6 P3 (0,25;1,0) 2.5 2.4 2.6 Losses (%) P4 (0,9;0,5) 3.5 3.4 3.6 P5 (0,5;0,5) 2.2 2.1 2.0 P6 (0,5;0,25) 1.7 1.7 1.8 P7 (0,25;0,25) 0.9 0.9 0.9 Drive end Non drive end Bearing type 6319 C3 6316 C3 WSeal Sealing WSeal 10000 h Lubrication interval 8000 h Lubricant amount 45 g 34 g Lubricant type Mobil Polyrex EM Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	26/03/2024			1/1	