

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Saw Arbor Motor Standard Efficiency Three-Phase Product code : 12214391

Frame	: 80M/MS	Locked rotor time	: 12s (cold) 7s (hot)
Output	: 5 HP (3.7 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: S1
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 208-230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 14.7-13.3/6.65 A	Protection degree	: IP54
L. R. Amperes	: 118-106/53.2 A	Cooling method	: IC411 - TEFC
LRC	: 8.0	Mounting	: B3R(D)
No load current	: 6.35-5.74/2.87 A	Rotation ¹	: CCW
Rated speed	: 3470 rpm	Noise level ²	: 62.0 dB(A)
Slip	: 3.61 %	Starting method	: Direct On Line
Rated torque	: 7.57 ft.lb	Approx. weight ³	: 99.4 lb
Locked rotor torque	: 340 %		
Breakdown torque	: 409 %		
Insulation class	: F		
Service factor	: 1.00		
Moment of inertia (J)	: 0.0978 sq.ft.lb		
Design	: N		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	81.2	82.0	84.5	85.0	Max. traction	: 149 lb
Power Factor	0.42	0.66	0.77	0.82	Max. compression	: 248 lb

	Drive end	Non drive end
Bearing type	: 6307 ZZ	: 6207 ZZ
Sealing	: Without Bearing Seal	: Without Bearing Seal
Lubrication interval	: -	: -
Lubricant amount	: -	: -
Lubricant type	: Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1 Revision		
Checked by				
Date	27/03/2024			