DATA SHEET



Three Phase Induction Motor - Squirrel Cage Customer Product line : W22 Tru-Metric IE2 Three-Phase Product code: 13025530 Frame : 28s (cold) 16s (hot) : 225S/M Locked rotor time Output : 30 HP (22 kW) Temperature rise : 80 K Poles Duty cycle : S1 : 8 Frequency : 50 Hz Ambient temperature : -20°C to +40°C Rated voltage : 380 V Altitude : 1000 m.a.s.l. Rated current : 44.1 A Protection degree : IP55 : 269 A Cooling method : IC411 - TEFC L. R. Amperes LRC : 6.1 Mounting : B3L(E) : Both (CW and CCW) No load current : 16.5 A Rotation¹ Rated speed : 730 rpm Noise level² : 56.0 dB(A) Slip : 2.67 % Starting method : Direct On Line Rated torque : 216 ft.lb Approx. weight3 : 842 lb Locked rotor torque : 170 % Breakdown torque : 210 % Insulation class : F Service factor : 1.15 Moment of inertia (J) : 23.0 sq.ft.lb Design : N Output 50% 75% 100% Foundation loads Efficiency (%) 91.9 91.4 91.8 92.0 91.4 92.2 Max. traction : 1224 lb 91.7 92.4 92.4 Power Factor 0.70 0.64 0.81 0.76 0.83 0.80 Max. compression : 2066 lb 0.65 0.77 0.81 Losses at normative operating points (speed;torque), in percentage of rated output power P1 (0,9;1,0) 7.8 P2 (0,5;1,0) 7.1 6.4 6.2 P3 (0,25;1,0) 6.6 5.9 5.8 Losses (%) P4 (0,9;0,5) 4.7 4.3 4.1 P5 (0,5;0,5) 3.1 2.8 2.7 P6 (0,5;0,25) 2.2 2.0 2.0 P7 (0,25;0,25) 1.6 1.4 1.4 Drive end Non drive end Bearing type 6314 C3 6314 C3 WSeal WSeal Sealing 20000 h 20000 h Lubrication interval Lubricant amount 27 g 27 g Lubricant type Mobil Polyrex EM Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	26/03/2024			1/1	