

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W40 JP Pump NEMA Premium Efficiency
Three-Phase

Product code : 14023476

Catalog # : 07518OT3E365JP-W40

Frame : 364/5JP
Output : 75 HP (55 kW)
Poles : 4
Frequency : 60 Hz
Rated voltage : 230/460 V
Rated current : 171/85.5 A
L. R. Amperes : 1163/581 A
LRC : 6.8x(Code G)
No load current : 61.0/30.5 A
Rated speed : 1780 rpm
Slip : 1.11 %
Rated torque : 221 ft.lb
Locked rotor torque : 220 %
Breakdown torque : 260 %
Insulation class : F
Service factor : 1.25
Moment of inertia (J) : 16.8 sq.ft.lb
Design : B

Locked rotor time : 25s (cold) 14s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP23
Cooling method : IC01 - ODP
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 69.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 797 lb

Output	25%		50%		75%		100%	
Efficiency (%)	94.4	93.7	94.5	93.8	95.0	94.2	95.0	94.2
	93.7	93.7	93.8	93.8	94.2	94.2	94.2	94.2
Power Factor	0.48	0.48	0.73	0.73	0.82	0.82	0.85	0.86
	0.43	0.40	0.69	0.66	0.80	0.77	0.84	0.83

Foundation loads
Max. traction : 1639 lb
Max. compression : 2436 lb

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6314 C3	6212 Z C3
Sealing	:	Without Bearing Seal	Without Bearing Seal
Lubrication interval	:	20000 h	20000 h
Lubricant amount	:	27 g	13 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	30/03/2024			
		Revision		