

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22Xec IE2 Three-Phase

Product code : 14351818

Catalog # : E00512EP3YAX132MF3-W

Area classification : ZONA 2/22, GRUPO IIC/IIIB, T3(200 °C)/T125 °C

Frame : 132M
Output : 5.5 kW (7.5 HP)
Poles : 6
Frequency : 50 Hz
Rated voltage : 380/660 V
Rated current : 13.0/7.48 A
L. R. Amperes : 78.0/44.9 A
LRC : 6.0
No load current : 6.80/3.92 A
Rated speed : 960 rpm
Slip : 4.00 %
Rated torque : 40.4 ft.lb
Locked rotor torque : 210 %
Breakdown torque : 240 %
Insulation class : F
Service factor : 1.00
Moment of inertia (J) : 1.43 sq.ft.lb
Design : N

Locked rotor time : 34s (cold) 19s (hot)
Temperature rise : 80 K
Duty cycle : S1
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : B3T
Rotation¹ : Both (CW and CCW)
Noise level² : 53.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 176 lb

Output	25%		50%		75%		100%	
Efficiency (%)	86.4	85.2	86.4	85.5	86.3	86.1	86.0	86.1
	83.9	83.5	84.6	85.5	85.7	87.5	86.2	89.5
Power Factor	0.33	0.29	0.56	0.51	0.68	0.64	0.75	0.72
	0.26	0.28	0.47	0.49	0.61	0.62	0.69	0.69

Foundation loads
Max. traction : 548 lb
Max. compression : 723 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	15.8	15.7	15.6	11.4
	P2 (0,5;1,0)	14.3	14.2	14.1	10.3
	P3 (0,25;1,0)	14.0	13.8	13.7	10.1
	P4 (0,9;0,5)	7.5	7.4	7.4	5.4
	P5 (0,5;0,5)	5.7	5.7	5.6	4.1
	P6 (0,5;0,25)	4.0	4.0	3.9	2.9
	P7 (0,25;0,25)	3.1	3.1	3.0	2.2

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type :		6308 ZZ	6207 ZZ
Sealing :		V'Ring	V'Ring
Lubrication interval :		-	-
Lubricant amount :		-	-
Lubricant type :		Mobil Polyrex EM	

Notes:

EAC
TC RU C-BR.AA87.B.00977/22
2Ex ec IIC T3 Gc X
Ex tc IIIB T125°C Dc X
ООО «НАИО ЛЦБЭ»
IECEX
IECEX BAS 10.0099X
Ex ec IIC T3 Gc
Ex tc IIIB T125°C Dc

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 3		
Checked by				
Date	27/03/2024			
			Revision	

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 3	Revision
Checked by					
Date	27/03/2024				

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	140 °C
2	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 3 / 3	Revision
Checked by					
Date	27/03/2024				