

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22Xdb IE3 Three-Phase

Product code : 12430654

Area classification : ZONA 1, GRUPO IIB, T4 (135 °C)

Catalog # : E01118XT3YAX160MF3-W

Frame : 160M/L
Output : 11 kW (15 HP)
Poles : 4
Frequency : 50 Hz
Rated voltage : 380/660 V
Rated current : 21.5/12.4 A
L. R. Amperes : 151/86.7 A
LRC : 7.0
No load current : 9.00/5.18 A
Rated speed : 1475 rpm
Slip : 1.67 %
Rated torque : 52.6 ft.lb
Locked rotor torque : 240 %
Breakdown torque : 270 %
Insulation class : F
Service factor : 1.00
Moment of inertia (J) : 3.49 sq.ft.lb
Design : N

Locked rotor time : 25s (cold) 14s (hot)
Temperature rise : 80 K
Duty cycle : S1
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP56
Cooling method : IC411 - TEFC
Mounting : B3T
Rotation¹ : Both (CW and CCW)
Noise level² : 61.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 447 lb

Output	25%		50%		75%		100%	
Efficiency (%)	91.3	90.7	91.4	90.7	91.4	91.6	91.4	91.4
	90.4	90.1	90.6	90.5	91.4	92.2	91.4	92.4
Power Factor	0.43	0.40	0.69	0.65	0.80	0.77	0.85	0.83
	0.36	0.37	0.61	0.62	0.74	0.75	0.81	0.81

Foundation loads
Max. traction : 520 lb
Max. compression : 984 lb

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	9.2	9.2	9.2	8.0
	P2 (0,5;1,0)	8.1	8.1	8.1	7.1
	P3 (0,25;1,0)	7.8	7.8	7.8	6.8
	P4 (0,9;0,5)	4.4	4.4	4.4	3.9
	P5 (0,5;0,5)	3.2	3.2	3.2	2.8
	P6 (0,5;0,25)	2.2	2.2	2.2	1.9
	P7 (0,25;0,25)	1.6	1.6	1.6	1.4

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6309 C3	6308 C3
Sealing	:	Oil Seal	Lip Seal
Lubrication interval	:	20000 h	20000 h
Lubricant amount	:	13 g	11 g
Lubricant type	:	Mobil Polyrex EM	

Notes:

ATEX
INERIS 22ATEX0025X
CML 23UKEX1256X
II 2G Ex db IIB T4 Gb
EAC
EAЭC RU C-BR.AA87.B.00379/20
1Ex db IIB T4 Gb X
ООО «НАННО ЦСВЭ»
IECEX
IECEX INE 22.0044X
Ex db IIB T4 Gb

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 3		
Checked by				
Date	27/03/2024			
		Revision		

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 2 / 3	Revision
Checked by					
Date	27/03/2024				

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	150 °C

Space heater information

Voltage: 200 - 240 V

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page 3 / 3	Revision
Checked by					
Date	27/03/2024				