DATA SHEET

Three Phase Induction Motor - Squirrel Cage



	:							
Product line	: W22 Tru-Metric IE3 Three-F		E3 Three-Phase	Product co Catalog # :		11567399 03036ET3Y200L-W22		
Frame		: 200L		Locked rotor time		: 34s (cold)	19s (hot)	
Output	: 40 HP (30 kW)			Temperature rise		: 80 K		
Poles	: 2			Duty cycle		: S1		
Frequency	: 50 Hz		Ambient temperatu	ure	: -20°C to +4	40°C		
Rated voltage	: 380 V		Altitude		: 1000 m.a.s.l.			
Rated current	: 55.3 A		Protection degree		: IP55			
L. R. Amperes		: 415 A		Cooling method		: IC411 - TEFC		
LRC		: 7.5		Mounting		: B3L(E)		
No load current		: 17.0 A		Rotation ¹		: Both (CW and CCW)		
Rated speed		: 2960 rpr	n	Noise level ²		: 72.0 dB(A)		
Slip		: 1.33 %		Starting method		: Direct On I	_ine	
Rated torque		: 71.0 ft.lb)	Approx. weight ³		: 580 lb		
		: 270 %						
Breakdown torque		: 270 %						
Insulation class		: F						
	Service factor : 1.25		·					
Moment of inertia (J)	: 4.44 sq.	tt.Ib					
Design		: N						
	50%	75%	100%	Foundation loads				
, ,	93.1 92.6	93.6 93.		Max. traction	: 5	521 lb		
	91.0	92.4	93.0					
	0.77 0.69	0.85 0.7		Max. compression	: 1	1101 lb		
	0.73	0.81	0.85					
Losses at normative				entage of rated output	<u>- </u>			
	P1 (0,9		6.4	6.4	7.0			
	P2 (0,5		4.3	4.3	4.8			
L 2000 - (0/)	P3 (0,2		3.7	3.7	4.1			
Losses (%)	P4 (0,9		4.1	4.1	4.5			
	P5 (0,5		2.2	2.2	2.4			
	P6 (0,5;		1.6	1.6	1.8			
	P7 (0,25	,∪,∠5)	0.9	0.9	1.0			
			Drive end	Non dri				
Bearing type	:		6312 C3		2 C3			
Sealing	:		V'Ring		Ring			
Lubrication interval	:		12000 h		000 h			
	:		21 g		3 g			
Lubricant amount Lubricant type			IVIC	bil Polyrex EM				

- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

()					
Rev.		Changes Summary	Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	26/03/2024	1		1/1	