

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel NEMA Premium Efficiency
Three-Phase

Product code : 12677339

Catalog # : 01018ET3ER215TC-S

Frame : 213/5TC
Output : 10 HP (7.5 kW)
Poles : 4
Frequency : 60 Hz
Rated voltage : 230/460 V
Rated current : 24.4/12.2 A
L. R. Amperes : 171/85.4 A
LRC : 7.0x(Code H)
No load current : 11.1/5.54 A
Rated speed : 1760 rpm
Slip : 2.22 %
Rated torque : 29.8 ft.lb
Locked rotor torque : 250 %
Breakdown torque : 300 %
Insulation class : F
Service factor : 1.15
Moment of inertia (J) : 1.07 sq.ft.lb
Design : B

Locked rotor time : 27s (cold) 15s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Protection degree : IP55
Cooling method : IC411 - TEFC
Mounting : W-6
Rotation¹ : Both (CW and CCW)
Noise level² : 60.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 142 lb

Output	25%	50%	75%	100%
--------	-----	-----	-----	------

Efficiency (%)	90.2	91.0	91.0	91.7
Power Factor	0.41	0.67	0.78	0.84

Foundation loads

Max. traction : 434 lb
Max. compression : 576 lb

	Drive end	Non drive end
Bearing type	6208 ZZ	6206 ZZ
Sealing	V'Ring	Without Bearing Seal
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	Mobil Polyrex EM	

Notes:

USABLE @208V 27.0A SF 1.00 SFA 27.0A

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 1		
Checked by				
Date	26/03/2024			
		Revision		