DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer Product line : Multimounting IE3 Three-Phase Product code: 13984841 Catalog #: 00718ET3YAL132M-W22 Frame : 132M Locked rotor time : 23s (cold) 13s (hot) Output : 10 HP (7.5 kW) Temperature rise : 80 K Poles : 4 Duty cycle : S1 Frequency : 50 Hz Ambient temperature : -20°C to +40°C Rated voltage : 380 V Altitude : 1000 m.a.s.l. Protection degree : IP55 Rated current : 14.5 A : IC411 - TEFC L. R. Amperes : 123 A Cooling method **LRC** : 8.5 Mounting : B3L(E) : Both (CW and CCW) No load current : 6.20 A Rotation¹ Rated speed : 1460 rpm Noise level² : 56.0 dB(A) Slip : 2.67 % Starting method : Direct On Line Rated torque : 36.0 ft.lb Approx. weight³ : 149 lb Locked rotor torque : 220 % Breakdown torque : 300 % : F Insulation class Service factor : 1.25 Moment of inertia (J) : 1.52 sq.ft.lb Design : N 25% Output 50% 75% 100% Foundation loads Efficiency (%) 91.0 90.0 91.0 90.5 91.5 91.4 91.2 91.7 Max. traction : 628 lb 89.4 90.2 91.0 91.7 Power Factor 0.43 0.37 0.70 0.64 0.81 0.76 0.86 0.81 Max. compression : 777 lb 0.38 0.65 0.76 0.81 Losses at normative operating points (speed;torque), in percentage of rated output power P1 (0,9;1,0) 9.4 8.8 8.8 P2 (0,5;1,0) 7.4 7.0 7.0 P3 (0,25;1,0) 6.8 6.3 6.3 Losses (%) P4 (0,9;0,5) 5.6 5.2 5.2 P5 (0,5;0,5) 3.7 3.5 3.5 P6 (0,5;0,25) 2.8 2.7 2.7 P7 (0,25;0,25) 1.9 1.8 Non drive end **Drive** end 6207 ZZ Bearing type 6308 ZZ V'Ring V'Ring Sealing Lubrication interval Lubricant amount Lubricant type Mobil Polyrex EM Notes: This revision replaces and cancel the previous one, which These are average values based on tests with sinusoidal must be eliminated. power supply, subject to the tolerances stipulated in NEMA (1) Looking the motor from the shaft end. MG-1. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load. Rev. **Changes Summary** Performed Checked Date Performed by Checked by Page Revision

1/1

26/03/2024

Date