

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage



Customer :

Product line : W22 IE2 Three-Phase

Product code : 14414751  
Catalog # : E01112EP3Y160LF3-W22

Frame	: 160L	Locked rotor time	: 27s (cold) 15s (hot)
Output	: 11 kW (15 HP)	Temperature rise	: 80 K
Poles	: 6	Duty cycle	: S1
Frequency	: 50 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 380/660 V	Altitude	: 1000 m.a.s.l.
Rated current	: 23.6/13.6 A	Protection degree	: IP55
L. R. Amperes	: 142/81.5 A	Cooling method	: IC411 - TEFC
LRC	: 6.0	Mounting	: B3T
No load current	: 13.0/7.48 A	Rotation <sup>1</sup>	: Both (CW and CCW)
Rated speed	: 975 rpm	Noise level <sup>2</sup>	: 57.0 dB(A)
Slip	: 2.50 %	Starting method	: Direct On Line
Rated torque	: 79.5 ft.lb	Approx. weight <sup>3</sup>	: 300 lb
Locked rotor torque	: 270 %		
Breakdown torque	: 300 %		
Insulation class	: F		
Service factor	: 1.00		
Moment of inertia (J)	: 3.95 sq.ft.lb		
Design	: N		

Output	25%		50%		75%		100%		Foundation loads	
Efficiency (%)	87.6	86.6	88.0	87.0	88.5	88.5	88.7	88.7	Max. traction	: 1108 lb
	85.5	86.5	86.0	87.0	88.5	90.0	88.7	90.2		
Power Factor	0.35	0.32	0.62	0.58	0.73	0.70	0.80	0.77	Max. compression	: 1409 lb
	0.29	0.30	0.54	0.55	0.66	0.67	0.74	0.75		

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	12.4	12.4	12.4	10.6
	P2 (0,5;1,0)	10.7	10.7	10.7	9.1
	P3 (0,25;1,0)	10.1	10.1	10.1	8.6
	P4 (0,9;0,5)	6.6	6.6	6.6	5.7
	P5 (0,5;0,5)	4.7	4.7	4.7	4.0
	P6 (0,5;0,25)	3.5	3.5	3.5	3.0
	P7 (0,25;0,25)	2.5	2.5	2.5	2.1

		<u>Drive end</u>	<u>Non drive end</u>
Bearing type	:	6309 ZZ C3	6209 ZZ C3
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes:

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in IEC 60034-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by		Page 1 / 2 Revision		
Checked by				
Date	26/03/2024			

DATA SHEET

Three Phase Induction Motor - Squirrel Cage



Customer :

Thermal protection

ID	Application	Type	Quantity	Sensing Temperature
1	Winding	Thermistor - 2 wires	1 x Phase	155 °C

Rev.	Changes Summary		Performed	Checked	Date
Performed by				Page	Revision
Checked by				2 / 2	
Date	26/03/2024				