



AUSTRALIA, NEW ZEALAND 15A-250V TYPE I OUTLET
AS/NZS 3112, AS/NZS 4417, (AU2-15R)
NOTE: OUTLET ACCEPTS 10A and 15A
AUSTRALIAN / NEW ZEALAND PLUGS

Note: RJ11 JACK IS TECHNICALLY AN
RJ12 JACK IN THAT IT HAS ALL 6 CONTACTS.
IT IS SUITABLE FOR USE WITH ALL RJ11 AND
RJ12 APPLICATIONS.

These devices shall be mounted on enclosures having adequate strength and
thickness and with adequate spacing provided. Seal rating is based on
mounting to a surface that is clean, flat and smooth.

STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED		
CONN. TYPE	EXTERIOR	INTERIOR
RJ45	CAT. 6 JACK	CAT. 6 JACK
RJ11	JACK	JACK

OPERATING TEMPERATURE: (0°C / +50° C (+32° F / +122° F))

MOUNTING KIT ORDERED
SEPARATELY CONTAINS
M4x0.7 SS SCREW, NYLON WASHER,
SPLIT LOCKWASHER AND M4 NUT
P/N: D-PIC-MT

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.

HOUSING MATERIALS	
BODY:	EPOXY COATED DIE CAST ALUMINUM
GASKET:	THERMOPLASTIC ELASTOMER
HANDLE:	POLYAMIDE
LEVERS:	STAINLESS STEEL

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MM]	DRAWN BY	DCG
	DRAWN DATE	07/14/2021
	CHECKED BY	DCG
	CHECK DATE	07/16/2021
COMMENTS:		
DO NOT SCALE DRAWING		

PIC RATINGS/SPECIFICATIONS	
VOLTS:	250V
AMPS:	3A
NEMA/UL EN 60529:	4, 4X, 12 IP65
MOUNTING SCREW SIZE:	M4 (8-32) (304 or 316SS for 4X)
MOUNTING SCREW TORQUE:	1.2~1.8N-m (0.9~1.3 Lb-Ft)
INCOMING POWER WIRE SIZE:	0.5 ~ 4.0 sq mm / 20-12AWG
WIRE STRIP LENGTH:	10 ~ 11 mm

MENCOM CORPORATION

TITLE:
AUS 10A RCPT;RJ11;RJ45;3A;32

SIZE	DWG. NO.	REV
B	DAS-RJ11-RJ45-R-32	C
SCALE: 2:3	WEIGHT:	SHEET 1 OF 1