				[126] 5.0										
						[92] 3.6								
										X				
					9 PIN	D-SUB CONFIR	GURED							
	-	PANEL CUT([88] 3.46		[4.5] Ø.18	9 PIN MALI	I D-SUB CONFIRC E EXTERIOR/ FEM	GURED 1ALE INTERI	OR		thickness and with	n adequate spacing	iclosures having adequ provided. Seal rating is		
					9 PIN MALI	I D-SUB CONFIRG E EXTERIOR/ FEM	GURED 1ALE INTERI	OR		thickness and with	h adequate spacing face that is clean, fla	provided. Seal rating is	based on	
	0	[88]		Ø.18	9 PIN MALI	I D-SUB CONFIRG E EXTERIOR/ FEM	GURED 1ALE INTERI	OR		thickness and with mounting to a surf	h adequate spacing face that is clean, fla	provided. Seal rating is at and smooth. NGS/SPECIFICAT	based on	
	0	[88]		Ø.18	9 PIN MALI	I D-SUB CONFIRG E EXTERIOR/ FEM	GURED ALE INTERI	HOUSING M		thickness and with mounting to a surf VOLTS: AMPS:	h adequate spacing face that is clean, fla	provided. Seal rating is at and smooth. NGS/SPECIFICAT 125V 3A	based on	
	0	[88]	OUT	Ø.18	9 PIN MALI	I D-SUB CONFIRG E EXTERIOR/ FEM	GURED ALE INTERIO	HOUSING M	ATED DIE CAST	thickness and with mounting to a surf VOLTS: AMPS: SCCR:	h adequate spacing face that is clean, fla PIC RATIN	provided. Seal rating is at and smooth. NGS/SPECIFICAT 125V 3A 0.2kA	based on	
	0	[88] 3.46	OUT	φ.18 4X	9 PIN MALI	I D-SUB CONFIRG E EXTERIOR/ FEM	ALE INTERI	HOUSING M EPOXY CO ALUMINUM THERMOP	DATED DIE CAST 1 LASTIC ELASTOMER	thickness and with mounting to a surf VOLTS: AMPS: SCCR: NEMA/UL I MOUNTING SC	n adequate spacing face that is clean, fla PIC RATIN EN 60529: CREW SIZE:	provided. Seal rating is at and smooth. NGS/SPECIFICAT 125V 3A 0.2kA 4, 4X, 12 M4 (8-32)	based on TONS IP65 (304 or 316SS fc	
		[88] 3.46 [76]	OUT	Ø.18 4X [65]	9 PIN MALI	I D-SUB CONFIRG E EXTERIOR/ FEM	ALE INTERI BODY: GASKET: HANDLE:	HOUSING M EPOXY CO ALUMINUM THERMOP POLYAMIE	DATED DIE CAST 1 LASTIC ELASTOMER DE	thickness and with mounting to a surf VOLTS: AMPS: SCCR: NEMA/UL I MOUNTING SC MOUNTING SC	n adequate spacing face that is clean, fla PIC RATIN EN 60529: CREW SIZE: CREW TORQU	provided. Seal rating is at and smooth. NGS/SPECIFICAT 125V 3A 0.2kA 4, 4X, 12 M4 (8-32) E: 1.2~1.8N-	based on IONS IP65 (304 or 316SS fc -m (0.9~1.3 Lb-Ft	t)
	0	[88] 3.46 [76]	OUT	Ø.18 4X [65]	MALI	D-SUB CONFIRG E EXTERIOR/ FEM	ALE INTERI BODY: GASKET: HANDLE: LEVERS:	HOUSING M EPOXY CO ALUMINUM THERMOP POLYAMIE STAINLES	DATED DIE CAST A LASTIC ELASTOMER DE S STEEL (+14° F / +140° F)	thickness and with mounting to a surf VOLTS: AMPS: SCCR: NEMA/UL I MOUNTING SC MOUNTING SC INCOMING PC	n adequate spacing face that is clean, fla PIC RATIN EN 60529: CREW SIZE: CREW TORQU DWER WIRE SI	provided. Seal rating is at and smooth. NGS/SPECIFICAT 125V 3A 0.2kA 4, 4X, 12 M4 (8-32) E: 1.2~1.8N-	l IP65 (304 or 316SS fc m (0.9~1.3 Lb-Ft sq mm / 20-12AV	t)
		[88] 3.46 [76]	OUT	Ø.18 4X [65]	MALI	E EXTERIOR/ FEM	ALE INTERI BODY: GASKET: HANDLE: LEVERS: RATURE: (-10	HOUSING M EPOXY CC ALUMINUN THERMOP POLYAMIE STAINLES 0°C / +60° C	DATED DIE CAST A LASTIC ELASTOMER DE S STEEL (+14° F / +140° F) UNLESS OTHERWISE SPECIFIED	thickness and with mounting to a surf VOLTS: AMPS: SCCR: NEMA/UL I MOUNTING SC MOUNTING SC MOUNTING SC INCOMING PC	A adequate spacing face that is clean, fit PIC RATIN EN 60529: CREW SIZE: CREW TORQU DWER WIRE SI ENGTH: DMEN	provided. Seal rating is at and smooth. NGS/SPECIFICAT 125V 3A 0.2kA 4, 4X, 12 M4 (8-32) E: 1.2~1.8N- ZE: 0.5 ~ 4.0	l IP65 (304 or 316SS fc m (0.9~1.3 Lb-Ft sq mm / 20-12AV	t)
		[88] 3.46 [76] 2.99	OUT	Ø.18 4X [65]	MALI OI MC SEF	E EXTERIOR/ FEM PERATING TEMPER DUNTING KIT ORDERE PARATELY CONTAINS	BODY: GASKET: HANDLE: LEVERS: RATURE: (-10 S	HOUSING M EPOXY CO ALUMINUM THERMOP POLYAMIE STAINLES 0°C / +60° C	DATED DIE CAST A LASTIC ELASTOMER DE S STEEL (+14° F / +140° F)	thickness and with mounting to a surf VOLTS: AMPS: SCCR: NEMA/UL I MOUNTING SC MOUNTING SC INCOMING PC) WIRE STRIP L	A adequate spacing face that is clean, fla PIC RATIN EN 60529: CREW SIZE: CREW TORQU DWER WIRE SI ENGTH: D 2018	provided. Seal rating is at and smooth. NGS/SPECIFICAT 125V 3A 0.2kA 4, 4X, 12 M4 (8-32) E: 1.2~1.8N- ZE: 0.5 ~ 4.0 10 ~ 11 m	l IP65 (304 or 316SS fc m (0.9~1.3 Lb-Ft sq mm / 20-12AV	t)
		[88] 3.46 [76]		Ø.18 4X [65]	MALI OI MC SEF M4 SPI	E EXTERIOR/ FEM PERATING TEMPER DUNTING KIT ORDERE PARATELY CONTAINS IX0.7 SS SCREW, NYLG	ALE INTERI BODY: GASKET: HANDLE: LEVERS: RATURE: (-10 ED S ON WASHER,	HOUSING M EPOXY CC ALUMINUM THERMOP POLYAMIE STAINLES 0°C / +60° C CUUUS LISTED ENCL ACC.	DATED DIE CAST A LASTIC ELASTOMER DE S STEEL (+14° F / +140° F) UNLESS OTHERWISE SPECIFIED	thickness and with mounting to a surf VOLTS: AMPS: SCCR: NEMA/UL I MOUNTING SC MOUNTING SC MOUNTING SC INCOMING PC) WIRE STRIP L CORAWN BY GC DRAWN DATE 11/21/	A adequate spacing face that is clean, fit PIC RATIN EN 60529: CREW SIZE: CREW TORQU DWER WIRE SI ENGTH: D 2018 D 2018 TITLE:	provided. Seal rating is at and smooth. NGS/SPECIFICAT 125V 3A 0.2kA 4, 4X, 12 M4 (8-32) E: 1.2~1.8N- ZE: 0.5 ~ 4.0 10 ~ 11 m NCOM CORP	l IP65 (304 or 316SS fc m (0.9~1.3 Lb-Ft sq mm / 20-12AV m PORATION	t) WG
		[88] 3.46 [76] 2.99 [110]		Ø.18 4X [65]	MALI OI MC SEF M4 SPL P/M	E EXTERIOR/ FEM PERATING TEMPER DUNTING KIT ORDERE PARATELY CONTAINS IX0.7 SS SCREW, NYLO LIT LOCKWASHER AN N: D-PIC-MT	ALE INTERI BODY: GASKET: HANDLE: LEVERS: RATURE: (-10 ED S ON WASHER,	HOUSING M EPOXY CO ALUMINUM THERMOP POLYAMIE STAINLES 0°C / +60° C	DATED DIE CAST A LASTIC ELASTOMER DE S STEEL (+14° F / +140° F) UNLESS OTHERWISE SPECIFIED	thickness and with mounting to a surf VOLTS: AMPS: SCCR: NEMA/UL I MOUNTING SC MOUNTING SC MOUNTING SC INCOMING PC) WIRE STRIP L DRAWN BY GC DRAWN DATE 11/21/ CHECKED BY GC	A adequate spacing face that is clean, fit PIC RATIN EN 60529: CREW SIZE: CREW TORQU DWER WIRE SI ENGTH: D 2018 D 2018 TITLE:	provided. Seal rating is at and smooth. NGS/SPECIFICAT 125V 3A 0.2kA 4, 4X, 12 M4 (8-32) E: 1.2~1.8N- ZE: 0.5 ~ 4.0 10 ~ 11 m	l IP65 (304 or 316SS fc m (0.9~1.3 Lb-Ft sq mm / 20-12AV m PORATION	t) WG
ΤΑΝΓ		[88] 3.46 [76] 2.99 [110] 4.33		Ø.18 4X [65] 2.56	MALI OI MC SEF M4 SPL P/N THE II	E EXTERIOR/ FEM PERATING TEMPER DUNTING KIT ORDERE PARATELY CONTAINS EX0.7 SS SCREW, NYLO IT LOCKWASHER AN N: D-PIC-MT ROPRIETARY AND CONFIDENTIAL FORMATION CONTAINED IN THIS	ALE INTERI BODY: GASKET: HANDLE: LEVERS: RATURE: (-10 ED S ON WASHER,	HOUSING M EPOXY CC ALUMINUM THERMOP POLYAMIE STAINLES 0°C / +60° C CUUUS LISTED ENCL ACC.	DATED DIE CAST A LASTIC ELASTOMER DE S STEEL (+14° F / +140° F) UNLESS OTHERWISE SPECIFIED	thickness and with mounting to a surf VOLTS: AMPS: SCCR: NEMA/UL I MOUNTING SC MOUNTING SC MOUNTING SC INCOMING PC) WIRE STRIP L DRAWN BY GC DRAWN DATE 11/21/ CHECKED BY GC	A adequate spacing face that is clean, fit PIC RATIN EN 60529: CREW SIZE: CREW TORQU DWER WIRE SI ENGTH: D 2018 D 2018 TITLE:	provided. Seal rating is at and smooth. NGS/SPECIFICAT 125V 3A 0.2kA 4, 4X, 12 M4 (8-32) E: 1.2~1.8N- ZE: 0.5 ~ 4.0 10 ~ 11 m NCOM CORP	l IP65 (304 or 316SS fc m (0.9~1.3 Lb-Ft sq mm / 20-12AV m PORATION	t) WG
		[88] 3.46 [76] 2.99 [110]		Ø.18 4X [65] 2.56	MALI OI MC SEF M4 SPL P/I F	E EXTERIOR/ FEM PERATING TEMPER DUNTING KIT ORDERE PARATELY CONTAINS EX0.7 SS SCREW, NYLO IT LOCKWASHER AN N: D-PIC-MT ROPRIETARY AND CONFIDENTIAL	ALE INTERI BODY: GASKET: HANDLE: LEVERS: RATURE: (-10 ED S ON WASHER,	HOUSING M EPOXY CC ALUMINUM THERMOP POLYAMIE STAINLES 0°C / +60° C CUUUS LISTED ENCL ACC.	DATED DIE CAST A LASTIC ELASTOMER DE S STEEL (+14° F / +140° F) UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND [MM]	thickness and with mounting to a surf VOLTS: AMPS: SCCR: NEMA/UL I MOUNTING SC MOUNTING SC MOUNTING SC INCOMING PC INCOMING PC DRAWN BY GC DRAWN BY GC DRAWN DATE 11/21/ CHECKED BY GC CHECK DATE 11/26/	A adequate spacing face that is clean, fix PIC RATIN EN 60529: CREW SIZE: CREW TORQU DWER WIRE SI ENGTH: D 2018 D 2018 D 2018 CREW TORQU DWER WIRE SI ENGTH: D 2018 CREW TORQU DWER WIRE SI ENGTH: D 2018 CREW SIZE DWO	provided. Seal rating is at and smooth. NGS/SPECIFICAT 125V 3A 0.2kA 4, 4X, 12 M4 (8-32) E: 1.2~1.8N- ZE: 0.5 ~ 4.0 10 ~ 11 m NCOM CORP	IDNS IDNS (304 or 316SS fc m (0.9~1.3 Lb-Ft sq mm / 20-12AV m PORATION INT; RJ45; 3,	t) WG

')	



