



Panel Interface Connectors

Popular PIC Models



Low Profile LP1 Housing | UL Type 4, 12 | IP65 Rating

Part Number	Description	Faceview	Part Number	Description	Faceview
LP1-E45UM-5	5 Port Unmanaged Ethernet Switch		LP1-DB9-USB-*	9 Pin D-Subs USB Form A Female with Cable to USB Form A Male LP1 Housing	
LP1-2RJ45	2 x RJ45 LP1 Housing		LP1-DCH1-RJ45-R	China 10 AMP Receptacle RJ45 3 AMP Reset LP1 Housing	
LP1-2USB-*	2 x USB Form A Female with Cable to USB Form A Male LP1 Housing		LP1-DP	Duplex Receptacle LP1 Housing	
LP1-2USB-AFAF	2 x USB A connections LP1 Housing		LP1-2DB9	2 x 9 Pin D-Sub LP1 Housing	
LP1-2USB-BFAF	2 x USB Female Form B to Female Form A LP1 Housing		LP1-DP1-2RJ45	Single Outlet 2 x RJ45 LP1 Housing	
LP1-4RJ45	4 x RJ45 LP1 Housing		LP1-DP1-2RJ45-R	Single Outlet 2 x RJ45 3 AMP Reset LP1 Housing	
LP1-DB25	25 Pin D-Sub LP1 Housing		LP1-DP1-DB9	Single Outlet 9 Pin D-Sub LP1 Housing	
LP1-DB9	9 Pin D-Sub LP1 Housing		LP1-DP1-DB9-RJ45	Single Outlet 9 Pin D-Sub RJ45 LP1 Housing	
LP1-DB9-RJ45	9 Pin D-Sub RJ45 LP1 Housing		LP1-DP1-R	Single Outlet 3 AMP Reset LP1 Housing	

* Length in feet. Standard cable lengths are 3,6 & 10 feet. Consult factory for other lengths.

Stainless steel UL Type 4X versions in development. Consult factory for more information.

PICs with International outlets are non-UL.