



Panel Interface Connectors

Popular PIC Models



Low Profile LP1 & LP2 Housing | UL Type 4, 12 | IP65 Rating

Part Number	Description	Faceview	Part Number	Description	Faceview
LP1-DP1-RJ45-R	Single Outlet RJ45 3 AMP Reset LP1 Housing		LP1-RJ45	RJ45 LP1 Housing	
LP1-DP1-RJ45-USB-AFAF-R	Single Outlet RJ45 USB Female Form A to Female Form A 3 AMP Reset LP1 Housing		LP1-RJ45-2USB-*	RJ45 2 x USB Form A Female with Cable to USB Form A Male LP1 Housing	
LP1-DP1-RJ45-USB-BFAF-R	Single Outlet RJ45 USB Female Form B to Female Form A 3 AMP Reset LP1 Housing		LP1-RJ45-USB-*	RJ45 USB Form A Female with Cable to USB Form A Male LP1 Housing	
LP1-DP1-USB-AFAF-R	Single Outlet USB Female Form A to Female Form A 3 AMP Reset LP1 Housing		LP1-USB-*	USB Form A Female with Cable to USB Form A Male LP1 Housing	
LP1-EP-R	Continental European Receptacle 3 AMP Reset LP1 Housing		LP1-USB-AFAF	USB Female Form A to Female Form A LP 1 Housing	
LP1-EP-RJ45	Continental European Receptacle RJ45 LP1 Housing		LP1-USB-BFAF	Single Outlet USB Female Form B to Female Form A LP1 Housing	
LP1-EP-RJ45-R	European Receptacle RJ45 3 AMP Reset LP1 Housing		LP2-2GF	2 x GFCI Receptacle LP2 Housing	
LP1-GF	GFCI Receptacle LP1 Housing		LP2-8RJ45	8 x RJ45 LP2 Housing	
LP1-RJ11	RJ11 LP1 Housing		LP2-DBR-DB9-RJ45-2USB-AFAF-R	Brazilian Receptacle 9 pin D-Sub RJ45 2xUSB A connections 3 AMP Reset LP2 Housing	

* Length in feet. Standard cable lengths are 3,6 & 10 feet. Consult factory for other lengths.

Stainless steel UL Type 4X versions in development. Consult factory for more information.

PICs with International outlets are non-UL.